TYPE · VFD CABLE · HALOGEN-FREE | 0.6/1 kV | 10 Variants

PROTOMONT EMV-FC HF Equivalent

FC-EMV-HF (N)SHXCÖU 0,6/1 kV

Halogen-free flexible cable for frequency converters (VFD) — symmetrical three-part earth, overall tinned copper braid screen and halogen-free HM4 sheath.

Document No. **FC-TDS-EMVH-2026-1A28** Revision **0** Issue date **12 October 2026**

Language **English (AU)**

01 Application & Product Overview

FC-EMV-HF (N)SHXCÖU is the halogen-free version of the EMC-screened VFD cable, for converter-to-motor connections where low smoke and no corrosive gases are required.

Three EPR-insulated phase cores and three green-yellow earth cores form a symmetrical construction. An overall tinned copper braid screen with more than 90 % coverage and a halogen-free, flame-retardant HM4 outer sheath complete the cable.

Typical applications

- Connections between frequency converters (VFD) and motors in underground mines
- Conveyor, pump and fan drives with variable speed
- EMC-compliant installations with long motor cables
- Tunnels, shafts and enclosed spaces requiring halogen-free cables
- Underground coal and hard-rock mines

10 variants
Conductor range 16 – 240 mm²

0.6/1 kV
Rated voltage, AC test 5 kV

Halogen-free
Low smoke, no corrosive gases

> 90 %
Copper braid screen coverage


Cross-reference

REFERENCE TYPE	⇄	FEICHUN EQUIVALENT
		FC-EMV-HF (N)SHXCÖU 0,6/1 kV

PROTOMONT EMV-FC (N)SHXCÖU 0,6/1 kV

Equivalent in construction and dimensions to PROTOMONT EMV-FC (N)SHXCÖU 0,6/1 kV.

02 Construction



FEICHUN · SECTION A–A · 0.6/1 kV

FC-EMV-HF (N)SHXCÖU

Doc. No. FC-TDS-EMVH-2026-1A28
Ref. 3×95 mm²
Rev. 0 · 2026-10-12 · 1st-angle · NTS

Drawing representative of the reference size; other sizes scale proportionally.

Pos.	Element	Material
1	Conductor	Annealed copper, finely stranded, class 5 (IEC 60228)
2	Insulation	EPR compound 3GI3 (DIN VDE 0207-20)
3	Earth conductor	Split into three green-yellow cores in the interstices (symmetrical)
4	Centre filler	Rubber filler
5	Inner sheath	Halogen-free rubber compound
6	EMC screen	Tinned copper braid, coverage > 90 %
7	Outer sheath	Halogen-free, flame-retardant HM4 / EVA compound

Drawing: 3×95 mm² reference size.

Construction details

Element	Description
Conductor	Finely stranded tinned annealed copper, class 5 (FS) to DIN EN 60228 / IEC 60228 / VDE 0295
Core insulation	EPR rubber (PROTOLON-type), special compound 3GI3 to DIN VDE 0207-20
Core identification	Phase cores light-coloured with black numerals 1, 2, 3; earth cores green-yellow
Protective earth	Split earth conductor: three insulated green-yellow earth cores of equal size laid in the outer interstices (symmetrical arrangement for EMC and balanced induced voltages)
Lay-up	Three phase cores and three earth cores stranded together; central filler where required
Inner sheath	Waterproof EPR rubber, special compound (GM1b type)
Screen	Overall braid of tinned copper wires, coverage > 90 %, for EMC
Outer sheath	Halogen-free crosslinked EVA rubber, special compound HM4 to DIN VDE 0207-23, yellow; low smoke, flame-retardant, abrasion-, oil-, ozone- and UV-resistant

03 Electrical, Thermal & Mechanical Data

Electrical parameters

Parameter	Value
Rated voltage U_0/U (Um)	0.6/1 (1.2) kV AC; also permitted for 640/1140 V
Max. operating voltage DC	0.9/1.8 kV
Max. peak voltage (converter operation)	2.4 kV
Test voltage	5 kV AC

Thermal & mechanical parameters

Parameter	Value
Max. conductor temperature	+90 °C
Max. short-circuit temperature	+250 °C
Ambient temperature, fixed installation	−40 °C to +80 °C

Parameter	Value
Current ratings	Per DIN VDE 0298-4, 30 °C ambient, three loaded conductors in air

Parameter	Value
Ambient temperature, flexing operation	−25 °C to +60 °C
Min. bending radius	4 × D fixed; 5 × D flexing (D = max. outer diameter), per DIN VDE 0298-3
Max. tensile load	15 N/mm², related to the total cross-section of the phase conductors
Max. torsional stress	±25 °/m
Screen	Tinned copper braid, optical coverage > 90 %; EMC-compliant
Operating capacitance / inductance	Approx. 420–730 nF/km; approx. 0.23–0.26 mH/km (see table)
Flame retardance	DIN EN 60332-1-2 / IEC 60332-1-2
Smoke density	DIN EN 61034-2 / IEC 61034-2
Corrosivity of combustion gases	DIN EN 60754-2 (formerly DIN EN 50267-2-2)
Oil resistance	DIN EN 60811-404 / IEC 60811-404
UV, ozone and moisture resistance	Resistant
Water resistance	Suitable for water immersion up to 500 m depth, water temperature max. 40 °C; seawater resistance excellent
Halogen-free	Yes

04 Dimensions, Weights & Ratings — 0.6/1 kV (10 variants)

Type designation cores × mm²	FeiChun part no.	Conductor Ø max. mm	Outer diameter min. mm	Outer diameter max. mm	Min. bending radius mm	Weight approx. kg/km	Max. tensile force N	R_{20} max. Ω/km	Current rating A	Short-circuit current kA (1 s)
3×16+3×2.5	FC-EMVH-001	5.4	24.4	27.4	137	1,200	720	1.240	99	2.29
3×25+3×4	FC-EMVH-002	6.3	28.2	31.2	156	1,710	1,125	0.795	131	3.57
3×35+3×16/3	FC-EMVH-003	7.5	30.5	33.5	168	2,020	1,575	0.565	162	5.00
3×50+3×25/3	FC-EMVH-004	8.9	36.0	39.0	195	2,850	2,250	0.393	202	7.15
3×70+3×35/3	FC-EMVH-005	10.6	41.2	44.2	221	3,850	3,150	0.277	250	10.01
3×95+3×50/3	FC-EMVH-006	12.1	45.7	48.7	244	4,810	4,275	0.210	301	13.58
3×120+3×70/3	FC-EMVH-007	14.1	48.7	52.7	264	5,940	5,400	0.164	352	17.16
3×150+3×70/3	FC-EMVH-008	16.0	55.7	59.7	299	7,270	6,750	0.132	404	21.45
3×185+3×95/3	FC-EMVH-009	17.8	60.4	64.4	322	8,700	8,325	0.108	461	26.45
3×240+3×120/3	FC-EMVH-010	20.2	68.2	72.2	361	11,500	10,800	0.0817	540	34.32

Current rating: DIN VDE 0298-4 values for flexible rubber cables at 30 °C ambient — apply the factors below for other ambient temperatures, grouping and multi-layer laying. Bending radius: 5 × D when moved, 4 × D fixed. Tensile force: 15 N/mm² × total phase cross-section. Further sizes and special designs are manufactured to order.

Ambient temperature factors (90 °C conductor)

°C	20	25	30	35	40	45	50
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82

Short-circuit rating

Permissible short-circuit current for 1 s: $I_k = 0.143$ kA/mm² × phase cross-section (EPR, 90 °C → 250 °C, tinned copper). For other durations t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ ($0.1\ s \le t \le 5\ s$).

05 Standards & Tests

Standard	Scope
DIN VDE 0250-812	Basis of design — flexible mining cables, low voltage
DIN EN 60228 / IEC 60228 / VDE 0295	Conductors, class 5 — class 5, tinned
DIN VDE 0207-20	Insulating compound 3GI3
DIN VDE 0207-21	Sheathing compounds

Routine & type tests

- AC voltage test 5 kV on every drum
- Conductor resistance and dimensional checks
- Continuity of earth, screen and control conductors
- Halogen-free verification (EN 60754-1/-2) and smoke density (EN 61034-2)
- Flame retardance (IEC 60332-1-2) and oil resistance (IEC 60811-404) of the outer sheath

Test documentation: each delivery is accompanied by a FeiChun in-house laboratory inspection certificate. Third-party witnessed testing can be arranged at the buyer's cost.

Standard	Scope
DIN VDE 0207-23	HM4
DIN VDE 0298-3	Use of cables — bending radii, tensile load
DIN VDE 0298-4	Current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation, single cable
DIN EN 60811-404 / IEC 60811-404	Oil resistance of sheath
DIN EN 61034-2 / IEC 61034-2	
DIN EN 60754-1/-2	formerly DIN EN 50267-2-2

06 Installation, Marking & Delivery

Installation notes

- Use symmetrical three-phase cable runs between converter and motor; terminate the overall copper braid 360° in EMC glands at both ends.
- Connect all three earth cores together at both ends to keep the earth system symmetrical.
- Observe the minimum bending radius: 4 × D fixed, 5 × D when moved.
- Keep tensile force within 15 N/mm² of the total conductor cross-section.
- Unwind tangentially from the delivery drum — never pull off over the flange; avoid loops and kinks.

Sheath marking

```
FEICHUN FC-EMV-HF (N)SHXCÖU [size] 0,6/1 kV [year] [serial no.] [metre mark]
```

Packing & delivery

Item	Standard
Drum	Steel or fumigated wooden drums, ends sealed with heat-shrink caps
Lengths	To order, single continuous length (no joints)
Production lead time	2–3 weeks after technical confirmation

Item	Standard
Warranty	Min. 3 years against manufacturing defects
Drum label	Type, size, length, gross/net weight, batch no., drum no.

07 Certifications & Quality

CE — LVD 2014/35/EU

Attestation No. M.2025.206.C116598 · EN 50525-1:2011+A1:2022 · UDEM International Certification · valid to 01.04.2030

EAC — TR CU 004/2011

Certificate No. EAЭC KG417/052.CN.02.15390 · GOST 31996-2012, GOST 31565-2012 · valid 24.10.2025–23.10.2030

UKCA — Verification

No. ICR/VC/HS2508110 · BS EN 50525-1:2011+A1:2022 · ICR Polska · valid to 17.08.2030

FeiChun also holds ATEX (Directive 2014/34/EU) documentation verification and IECEx / VDE related approvals for designated product families. Mine-specific approvals are arranged with the end user or local distributor where required. Certificate copies are available on request.

08 Trademark Notice & Intellectual Property

PROTOMONT® and the type designation PROTOMONT EMV-FC (N)SHXCÖU 0,6/1 kV are cited to identify the reference product of Prysmian Group, the trademark owner. They are used solely for technical cross-referencing; FeiChun Cables has no affiliation with, and is not endorsed by, the trademark owner. FC-EMV-HF is a FeiChun product designed to equivalent functional performance.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, redistribution or modification in whole or in part without written consent is prohibited. Technical data are subject to change without notice as part of continuous product development.

Technical & Sales Contact

Anhui FeiChun Special Cable Co., Ltd.

International Business Department

No. 1 Park, Private Science & Technology Park, Hefei National ETDZ, Hefei, Anhui, China

Technical: Tech@feichuncables.com

Mining & heavy industry: mining@feichuncables.com

Zihao Yang, Global Sales Manager:

zihao.yang@feichuncables.com

WhatsApp: +86 138 5512 3218

Web: www.feichuncables.com

Document Control

Doc. No. FC-TDS-EMVH-2026-1A28

Revision 0 — first issue

Date 12 October 2026

Product FC-EMV-HF (N)SHXCÖU 0,6/1 kV

Prepared — Technical Dept.	Checked — QA	Approved — Intl. Business

FEICHUN CABLE