FeiChun Special Cables
Anhui FeiChun Special Cable Co., Ltd. · Hefei, China

Technical Data Sheet
FC-TDS-BXP-2026-S3Q7

TDS · REELING CABLE | 0.6/1 kV | 4G16 mm² | Yellow outer sheath

Equivalent to BUFLEX X'PREM

FC-FLX™ BX-P 4G16 — Heavy-Duty Power Reeling Cable, 0.6/1 kV, Yellow

Rubber-insulated, anti-torsion braided reeling cable for motorised cable drums, gantry and overhead cranes — engineered as a direct equivalent to Nexans BUFLEX X'PREM 4G16 (Part No. 0426030 / Manufacturer Product Code 9426030).

Document No. **FC-TDS-BXP-2026-S3Q7** Revision **00** Issue date **28.09.2026**

Prepared for **QANBAR DYWIDAG Precast Concrete Co. Ltd., KSA**

1 Application

FC-FLX™ BX-P is designed for power supply to mobile equipment where the cable is repeatedly wound onto and paid off from motorised or spring-driven drums, and for high-cycle festoon and guided-trolley systems. The anti-torsion textile braid embedded between the two sheaths holds the cable geometry under combined tensile, bending and torsional stress, preventing corkscrewing and core displacement at high travel speeds.

- Gantry & portal cranes in precast yards
- Motorised cable reels
- Overhead travelling cranes
- Stacker / transfer cars
- Outdoor, UV & ozone exposure
- Oil-contaminated environments

> The yellow outer sheath provides high visibility on crane runways and yard floors, reducing the risk of vehicle strikes on the trailing section — an important safety feature for precast concrete handling yards with forklift and truck traffic.

2 Construction



FC-TDS-BXP-2026-S3Q7	
Rev. 00 · 28.09.2026	Scale ≈ 2 : 1
1st-angle proj.	Units: mm

Section A–A · FC-FLX™ BX-P 4G16 · schematic, not to exact scale

Pos.	Element	Material / design
1	Conductor	Bare annealed copper, finely stranded, Class 5 to IEC 60228 / VDE 0295
2	Insulation	EPR rubber compound type 3GI3 (VDE 0207-20), 90 °C
3	Central element	Textile / elastomer anti-strain filler
4	Inner sheath	Special rubber compound, type 5GM3, pressure-extruded into interstices
5	Anti-torsion braid	High-tenacity polyester textile braid, vulcanised between sheaths
6	Outer sheath	Heavy-duty polychloroprene (PCP) type 5GM5 (VDE 0207-21), yellow

Core identification: three black cores printed 1-2-3 plus one green/yellow protective earth core (to VDE 0293-308). Cores laid up with short lay length around the central element.

3 Dimensional data

Parameter	Value	Note
Number of cores × nominal cross-section	4 × 16 mm²	3 phases + PE (G/Y)
Conductor diameter (approx.)	5.6 mm	Class 5 flexible
Nominal insulation thickness	1.0 mm	IEC 60502-1 / VDE 0250-814
Nominal inner sheath thickness	1.2 mm	Over laid-up cores
Nominal outer sheath thickness	1.8 mm	Yellow PCP 5GM5
Overall diameter	25.5 ± 0.8 mm	Measured over outer sheath
Net cable weight (approx.)	1,060 kg/km	±5 %
Copper index	614 kg/km	For LME copper adjustment

4 Electrical data

Parameter	Value
Rated voltage U_0/U	0.6/1 kV AC
Maximum permissible AC voltage U_m	1.2 kV
Maximum DC voltage (to earth)	0.9 kV
Routine test voltage	3.5 kV AC, 5 min
Max. conductor resistance at 20 °C	1.21 Ω/km
Insulation resistance at 20 °C	≥ 20 MΩ·km
Max. conductor temperature (operation)	90 °C
Max. short-circuit temperature (≤ 5 s)	250 °C
Short-circuit current, 1 s (approx.)	2.3 kA

Current-carrying capacity	Ampacity
Laid straight in free air, 30 °C, 3 loaded cores	100 A
Same, at 45 °C ambient (Jeddah summer design)	87 A
Wound on drum, 1 layer, 30 °C	80 A
Wound on drum, 2 layers, 30 °C	61 A
Wound on drum, 3 layers, 30 °C	49 A

Basis: DIN VDE 0298-4 (tables 11, 16 and 17). Apply ambient and reeling factors cumulatively.

Correction factors for ambient temperature (90 °C conductor)

Ambient °C	30	35	40	45	50	55	60
Factor	1.00	0.96	0.91	0.87	0.82	0.76	0.71

5 Mechanical & operating data

Parameter	Value	Note
Ambient temperature, flexing / reeling	−25 … +80 °C	Suitable for Red Sea coastal climate
Ambient temperature, fixed installation	−40 … +80 °C	
Min. bending radius, fixed	4 × D ≈ 102 mm	
Min. bending radius, reeling / free movement	5 × D ≈ 128 mm	Drum barrel
Min. bending radius, over guide rollers	7.5 × D ≈ 191 mm	S-bends: 10 × D
Maximum travel speed	180 m/min	Reeling and festoon duty
Max. dynamic tensile load on conductors	1,280 N	20 N/mm² × 64 mm²
Permissible torsional stress	± 25 °/m	Anti-torsion braid
Flame propagation	Flame retardant to IEC 60332-1-2 / EN 60332-1-2	
Oil resistance	EN 60811-404 (IRM 902, 24 h / 100 °C)	
UV, ozone & weather resistance	EN 50396 / HD 605 S2 — suitable for permanent outdoor use	
Water	AD7 (temporary immersion) — suitable for wet yard conditions	

6 Standards, compliance & testing

Design and material standards

DIN VDE 0250-814 (design basis) · IEC 60228 / VDE 0295 · VDE 0207-20 and 0207-21 · IEC 60502-1 · DIN VDE 0298-3 / 0298-4 (application and ampacity) · IEC 60332-1-2.

Conformity

CE marked, RoHS and REACH compliant. FeiChun factory certifications include VDE, CE, UKCA, EAC, ATEX and IECEx. Every drum is supplied with an in-house routine test report (conductor resistance, high-voltage test, dimensions). Third-party witness testing on request at buyer's cost.

7 Cross-reference

Requested item	FeiChun equivalent	Interchangeability
Nexans BUFLEX X'PREM 4G16, yellow, 0.6/1 kV — Part No. 0426030 / Mfr. code 9426030	**FC-FLX™ BX-P 4G16, yellow, 0.6/1 kV**	Same core configuration, voltage rating, conductor class, EPR/rubber-sheath system and anti-torsion design — suitable for the same drums, guides and cable glands (Ø 25.5 mm).

8 Marking & packing

Sheath marking (embossed or ink-jet, every metre): FEICHUN FC-FLX™ BX-P 4G16 0.6/1 kV CE — year of manufacture — metre counter.

Packing for this order: 1 × 400 m on one ISPM-15 fumigated wooden drum, approx. Ø 1,100 × 800 mm, approx. 0.97 m³; net weight approx. 424 kg, gross weight approx. 535 kg. Both cable ends sealed with heat-shrink caps; drum lagged with plywood battens for sea freight.

Trademark and intellectual-property notice. BUFLEX® and X'PREM are trademarks of Nexans; LAPP® is a trademark of Lapp Holding SE. They are cited solely to identify the product for which an equivalent is offered; FeiChun has no affiliation with these companies. FC-FLX™ is a trademark of Anhui FeiChun Special Cable Co., Ltd. This data sheet and its drawings are the intellectual property of FeiChun and are protected under the Copyright Law of the People's Republic of China and the Copyright Act 1968 (Cth), Australia. Data are typical values; FeiChun reserves the right to make technical improvements without notice.

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
No. 1 Park, Private Science & Technology Park, Hefei National Economic & Technological Development Zone, Hefei, Anhui, China
Web: **www.feichuncables.com**

Technical & commercial contacts
Technical: **Tech@feichuncables.com**
Mining & heavy-duty: **mining@feichuncables.com**
Zihao Yang, Global Sales Manager: **zihao.yang@feichuncables.com**
WhatsApp: **+86 138 5512 3218**

© 2026 Anhui FeiChun Special Cable Co., Ltd.