MINING REELING CONTROL CABLE · MOBILE MACHINERY | 0.6/1 kV | 5 sizes | CPE rubber

FC-MCR-R 12G 0.6/1 kV

Mining Reeling Control Cable 0.6/1 kV – 12-core reeling control cable, CPE rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, standards and installation guidance for 5 sizes.

Document no. FC-TDS-MC062-2026-9715-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

FC-MCR-R 12G is a 12-core reeling control cable rated 0.6/1 kV for cable reels on drill rigs, LHD machines, shuttle cars and mobile mining plant. It has fine-wire class 5 copper cores with halogen-free EPR/HEPR rubber insulation, an inner sheath and an outer sheath of chlorinated polyethylene (CPE) rubber, resistant to weather, ozone and oil. Core cross-sections: 0.75 – 4 mm².

Design

12 cores in concentric layers with a short lay length and polyester binder tape. Black cores carry white numbers; the green-yellow protective core lies in the outer layer. The cores are bound with halogen-free filler and covered by an inner sheath before the outer sheath is applied.

Typical applications

- Control, signal and measuring circuits of drill rigs, LHD machines, shuttle cars and mobile crushers supplied through a cable reel
- Spring-driven and motor-driven cable reels on mining machines, cable handlers and conveyor take-up systems
- Operation with repeated winding, unwinding and bending within the permitted bending radius
- Wet, muddy, oily and abrasive environments typical of underground headings and open pits
- Control cabinets, junction boxes and remote-control stations of mining machinery
- Open-pit and surface duty that calls for a rubber sheath with proven weather, ozone and oil resistance

5 sizes	0.6/1 kV	+90 °C	CPE rubber
Cross-section 0.75 – 4 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CPE rubber

Key features

- Fine-wire class 5 copper cores with insulation thickness to 0.6/1 kV for reliable operation on a reel
- Cores laid in concentric layers with a short lay length and polyester binder tape
- Number-printed black cores; green-yellow protective core in the outer layer (G types)
- CPE rubber sheath with proven weather, ozone and oil resistance
- Flame retardant to IEC 60332-1-2

Service notes for mining duty

- Route control cables on the reel in a separate channel from MV or unscreened power cables, or use the screened version.
- Strip the outer sheath only as far as required for termination and seal the cable entry against water.


© 2026 Anhui FeiChun Special Cable Co., Ltd.

02 Construction

FEICHUN · CROSS-SECTION A-A · 0.6/1 kV

FC-MCR-R

Sample size 12G1.5 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Bare annealed fine-wire copper, class 5 to IEC 60228
2	Insulation	Halogen-free EPR/HEPR rubber
3	Protective (PE) core	Class 5 copper, green-yellow insulation
4	Filler and binder tape	Halogen-free compound, polyester tape
5	Inner sheath	Halogen-free polymer compound
6	Outer sheath	Chlorinated polyethylene (CPE) rubber, resistant to weather, ozone and oil

The drawing shows size 12G1.5. Other sizes have the same construction with scaled dimensions.

Construction details

Conductor	Bare annealed fine-wire copper, class 5 to DIN EN 60228 / IEC 60228 / VDE 0295
Insulation	Halogen-free EPR/HEPR rubber to IEC 60502-1, maximum conductor temperature 90 °C
Core identification	Black cores with white numbers; green-yellow protective core in the outer layer
Stranding	Cores stranded in concentric layers with a short lay length; polyester binder tape
Inner sheath	Halogen-free polymer compound, extruded tightly over the stranded cores
Outer sheath	Chlorinated polyethylene (CPE) rubber, resistant to weather, ozone and oil

Sheath material

The chlorinated polyethylene (CPE) rubber sheath offers good resistance to weather, ozone and mineral oil with good mechanical robustness and flexibility to −30 °C in motion, at a favourable cost level. CPE contains halogen; where halogen-free cables are specified, select the PUR version of the same construction.

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	0.6/1 kV AC
Test voltage	3.5 kV AC, 5 min
Maximum operating voltage, DC	0.9/1.8 kV
Current-carrying capacity	To DIN VDE 0298-4 at 30 °C ambient; the table gives rated design values
Conductor resistance	Maximum at 20 °C, class 5 to IEC 60228

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C
Ambient temperature, fixed installation	−40 °C to +90 °C
Ambient temperature, in motion	−30 °C to +90 °C
Minimum bending radius	Fixed: 4 × D (D ≥ 8 mm), 3 × D (D < 8 mm); moving or reeling: 6 × D (D ≤ 12 mm), 8 × D (D ≤ 20 mm), 10 × D (D > 20 mm)
Maximum tensile load	15 N/mm² continuous, on the total copper cross-section of the power cores
Maximum travelling speed	60 m/min on a cable reel; higher speeds on request
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CPE rubber sheath)
UV and ozone resistance	Resistant
Mineral oil resistance	Resistant, IEC 60811-404

04 Dimensions, Weights and Rated Data – 0.6/1 kV (5 sizes)

Type designation cores × mm²	FeiChun article no.	Conductor Ø max mm	Outer Ø min mm	Outer Ø max mm	Min. bend radius mm	Weight approx. kg/km	Max. pull force N	R_{20} max Ω/km	Current per core A	I_k (1 s) kA
12G0.75	FC-MC062-001	1.2	15.3	16.3	130	295	135	26.0	8	0.107
12G1	FC-MC062-002	1.4	16.1	17.1	136	340	180	19.5	10	0.143
12G1.5	FC-MC062-003	1.7	17.5	18.5	148	430	270	13.3	12	0.214
12G2.5	FC-MC062-004	2.2	19.6	20.8	208	590	450	7.98	17	0.357
12G4	FC-MC062-005	2.7	22.0	23.4	234	810	720	4.95	23	0.572

Current-carrying capacity: rated design values to DIN VDE 0298-4 for flexible cables, free air, 30 °C ambient; values per core include the derating factor for the number of cores; for other ambient temperatures, grouping or layered winding on a reel, apply the factors below. Pull force = 15 N/mm² × total copper cross-section of the power cores. Diameters, dimensions and weights are nominal design values and vary within manufacturing tolerances; confirm critical dimensions before dimensioning reels, guides or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another short-circuit duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Reeling Performance and Reel Design Data

The values below support the dimensioning of the cable reel: minimum reel core diameter, copper weight for earthing and loop-resistance calculations, cable weight, and the rated current for the number of layers wound on the reel.

Type designation cores × mm²	Outer Ø max mm	Min. bend radius on reel, mm	Min. reel core Ø mm	Copper weight kg/km	Cable weight kg/100 m
12G0.75	16.3	130	260	80	29.5
12G1	17.1	136	272	107	34.0
12G1.5	18.5	148	296	160	43.0
12G2.5	20.8	208	416	267	59.0
12G4	23.4	234	468	430	81.0

Reel design guidance

- Minimum reel core diameter = 2 × minimum bending radius = 2 × minimum bending radius (outer diameter D).
- Fit a guide or level-wind that keeps the cable parallel to the reel axis to prevent crossing turns.
- Rated current falls with the number of layers on the reel because heat is not dissipated; see the layer factors below.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

06 Selection Guide and Sizing Aid

FC-MCR-R 12G covers 5 sizes. The smallest, 12G0.75, has an outer diameter of up to 16.3 mm and weighs about 295 kg/km; the largest, 12G4, has an outer diameter of up to 23.4 mm and weighs about 810 kg/km, 2.7 times as much. Across the range the rated current per core rises from 8 A to 23 A at 30 °C, and the minimum bending radius from 130 mm to 234 mm.

Example 1. A circuit carries 8 A per core at an ambient temperature of 40 °C. Required table current = 8 / 0.91 = 9 A per core. The smallest suitable size is 12G1 with 10 A per core.

Example 2. A circuit carries 15 A per core at an ambient temperature of 35 °C. Required table current = 15 / 0.96 = 16 A per core. The smallest suitable size is 12G2.5 with 17 A per core.

Type designation cores × mm²	Total copper mm²	Cable weight kg/100 m	Winding capacity m	Free-hanging length m (vertical)
12G0.75	9	29.5	16,050	46
12G1	12	34.0	14,745	53
12G1.5	18	43.0	12,500	64
12G2.5	30	59.0	9,880	77
12G4	48	81.0	7,530	90

Winding capacity is an indicative value for a reel with 2,500 mm flange diameter, 1,000 mm traverse width, core diameter equal to the minimum reel core diameter and 90 % fill; it is not a substitute for the reel manufacturer’s calculation. Free-hanging length = permissible pull ÷ (weight × 9.81); it is the length at which the cable’s own weight reaches the rated pull, without any safety factor for hoisting.

07 Engineering Profile by Size

Each size of FC-MCR-R 12G with the values that matter when sizing a circuit: dimensions, weight, copper share, heat and voltage drop at rated current, and the permissible pull. Voltage drop is for 100 m of cable at rated current with conductors at 90 °C (single-phase AC or DC round trip).

Choose 12G0.75 when the load is near 8 A: the conductor resistance is 26.00 Ω/km, the overall size is Ø 16.3 mm and the weight 295 kg/km. The minimum reel core is 260 mm and the 1 s short-circuit rating 0.11 kA. Reel and handling: at 12G0.75 the minimum reel core is 260 mm and the cable weighs 29.5 kg per 100 m, so a 500 m length weighs about 148 kg before the drum.

12G1: Ø 17.1 mm; bend radius 136 mm; weight 340 kg/km. Voltage drop at rated current (10 A) is 49.7 V per 100 m, loss 5.0 W/m, and the cable can support 53 m of its own length vertically at the rated pull of 180 N. Per 100 m, 12G1 contains 10.7 kg of copper and 23.3 kg of insulation, filler and sheath material, which sets the scrap value and the recycling split.

For 12G1.5 the design values are: Ø 18.5 mm, 430 kg/km, 270 N permissible pull, 12 A rated current. The copper accounts for 37% of the weight, and 4.9 W/m is dissipated at full load, so heat-sensitive reel layers should be derated as shown in section 04. Handling 12G1.5: 43.0 kg per 100 m, bending radius 148 mm; two people can lift a 20 m piece of about 8.6 kg.

For 12G2.5 the design values are: Ø 20.8 mm, 590 kg/km, 450 N permissible pull, 17 A rated current. The copper accounts for 45% of the weight, and 5.9 W/m is dissipated at full load, so heat-sensitive reel layers should be derated as shown in section 04. A 500 m length of 12G2.5 weighs about 295 kg; with a 416 mm minimum core the drum must be sized for that load.

Size 12G4 has a maximum conductor resistance of 4.95 Ω/km, a copper content of 430 kg/km and a minimum bending radius of 234 mm (reel core 468 mm). Short-circuit capability for 1 s is 0.57 kA. Expect 29.0 V of drop per 100 m at 23 A. Reel and handling: at 12G4 the minimum reel core is 468 mm and the cable weighs 81.0 kg per 100 m, so a 500 m length weighs about 405 kg before the drum.

08 Configuration Guidance and Variant Comparison

Typical case: a cable handler whose control loom must survive repeated winding at 148 mm radius. For this case FC-MCR-R 12G is a fit in the 12G1.5 size (Ø 18.5 mm).

CPE rubber is the economical rubber option for surface trailing and reeling duty where halogen-free materials are not required.

Rated 0.6/1 kV, the cable covers the common 400 V, 690 V and 1,000 V mining supplies.

In the drawn size 12G1.5 the cores fill 66% of the circle inside the inner sheath, the inner sheath is 0.8 mm thick and the outer sheath 1.8 mm, giving a total wall of 2.5 mm around a core bundle of Ø 13.0 mm.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

FC-MCR-R 12G is one of 360 datasheets in the mining reeling control cable group and one of 953 in the library. The next smaller core count, FC-MCR-R 10G, has an outer Ø of 18.0 mm at 1.5 mm² against 18.5 mm here. The next larger core count, FC-MCR-R 14G, measures 25.0 mm and weighs 640 kg/km (this model: 430 kg/km).

Element inventory and core layout

Element inventory of the drawn size 12G1.5: 12 elements with 18.0 mm² of copper in total. The 12 cores are stranded in 2 concentric layers (layer 1: 3 cores; layer 2: 9 cores), counted from the centre outwards, each layer with a short lay length and alternating lay direction. Keeping about 15 % of the cores as spare leaves 9 usable circuits plus the protective core; plan the core allocation before ordering because the number cannot be changed after manufacture.

Element	Quantity	Cross-section	Ø over insulation mm	Copper mm²
Power / main core	11	1.5 mm²	3.1	16.5
Protective (PE) conductor	1	1.5 mm²	3.1	1.5

Termination data (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Terminal row mm	Gland-to-bend straight mm
12G0.75	16.3	M32	ferrule	12	61	65
12G1	17.1	M32	ferrule	12	61	68
12G1.5	18.5	M32	ferrule	12	61	74
12G2.5	20.8	M32	ferrule	12	61	104
12G4	23.4	M40	ferrule	12	90	117

Gland, lug and terminal-row values are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

Comparison with related variants at size 12G1.5

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet FC-MCR-R 12G	–	18.5	430	270	12
FC-MCR-S 12G 0.6/1 kV	sheath	18.5 (+0%)	430 (+0%)	270 (+0%)	12 (+0%)
FC-MCR-A 12G 0.6/1 kV	sheath	18.5 (+0%)	395 (-8%)	270 (+0%)	12 (+0%)
FC-MCR-R 10G 0.6/1 kV	configuration	18.0 (-3%)	383 (-11%)	225 (-17%)	14 (+17%)
FC-MCR-R 14G 0.6/1 kV	configuration	25.0 (+35%)	640 (+49%)	315 (+17%)	12 (+0%)
FC-MCR-R-C 12G 0.6/1 kV	screen	19.5 (+5%)	500 (+16%)	270 (+0%)	12 (+0%)
FC-MCR-R-HT 12G 0.6/1 kV	tensile braid	20.0 (+8%)	480 (+12%)	1,960 (+626%)	12 (+0%)

Percentages show the change against this datasheet for the same cross-section; use them to judge what a change of sheath, voltage class, screen or tensile braid costs in size and weight.

09 Standards and Testing

Standard	Scope
DIN EN 60228 / IEC 60228 / VDE 0295	Conductors, class 5
IEC 60502-1	Insulation compound, power cables up to 1 kV
DIN VDE 0298-3	Application of cables – bending radii and tensile loads
DIN VDE 0298-4	Application of cables – current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation, single cable
DIN VDE 0293-308	Core identification
IEC 60811-404	Mineral oil immersion test

Routine and type tests

- AC voltage test on every reel length (routine test): 3.5 kV AC, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors and protective earth
- Bending, tensile tests (type test)
- Flame propagation (IEC 60332-1-2)

Test documentation: every delivery is accompanied by a test certificate from FeiChun’s own laboratory. Third-party witnessed tests can be arranged at the buyer’s cost.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

10 Installation, Marking and Delivery

Installation guidance

- Use a reel core diameter of at least twice the minimum bending radius; keep the cable free of loops and kinks while winding.
- Do not exceed the tensile load in the table; relieve the cable of tension at the reel hub and at the machine.
- Connect the protective core (G types) at both ends; terminate the screen 360° where fitted.
- Inspect the sheath regularly for abrasion and mechanical damage.

Sheath marking

FEICHUN FC-MCR-R [cross-section] 0.6/1 kV [year] [serial no.] [metre mark]

Packing and delivery

Reel	Steel or fumigated wooden reels; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Reel label	Type, cross-section, length, gross/net weight, batch no., reel no.

Ordering information

Order example: FC-MCR-R 12G1.5 0.6/1 kV – 500 m on one steel reel. When requesting a quotation, state the cable type, configuration, cross-section, voltage, length per piece, required standards and installation conditions.

11 Certification and Quality

All cable is subject to FeiChun’s quality control, with routine testing over 100 % of the delivered length. Certificates, type tests and third-party tests (for example partial discharge or compatibility with cable accessories) are provided per project requirement; copies of the records are available on request.

Mine-specific approvals (for example coal-mine safety marks, MSHA, or ATEX / IECEx for gassy atmospheres) are not implied by this datasheet; they depend on the project, the machine and the country and are arranged with the end user.

12 Related Datasheets

Variants of this cable with a different sheath, configuration or voltage. All datasheets are in PDF format.

- FC-MCR-S 12G 0.6/1 kV – 12-core reeling control cable, CSP rubber
- FC-MCR-A 12G 0.6/1 kV – 12-core reeling control cable, PUR low-temp
- FC-MCR-R 10G 0.6/1 kV – 10-core reeling control cable, CPE rubber
- FC-MCR-R 14G 0.6/1 kV – 14-core reeling control cable, CPE rubber
- FC-MCR-R-C 12G 0.6/1 kV – 12-core reeling control cable with overall tinned-copper braid screen, CPE rubber
- FC-MCR-R-HT 12G 0.6/1 kV – 12-core reeling control cable, with aramid tensile support braid, CPE rubber
- FC-MCR-R 8G 0.6/1 kV – 8-core reeling control cable, CPE rubber
- FC-MCR-R 16G 0.6/1 kV – 16-core reeling control cable, CPE rubber

Overview of all datasheets: Mining Reeling Control Cables 300/500 V and 0.6/1 kV

Frequently asked questions

What is FC-MCR-R 12G used for?
Typical applications include control, signal and measuring circuits of drill rigs, LHD machines, shuttle cars and mobile crushers supplied through a cable reel.

What are the outer diameter and minimum bending radius of 12G1.5?
The outer diameter is 17.5 to 18.5 mm and the minimum bending radius in moving or reeling operation is 148 mm (6 to 10 × D depending on diameter).

What minimum reel core diameter is needed for 12G1.5?
At least 296 mm, which is twice the minimum bending radius of 148 mm. A larger core diameter extends cable life.

What current can each core of 12G1.5 carry?
The table gives 12 A per core in free air at 30 °C ambient, already reduced for the number of cores; apply the ambient temperature factor and, on a reel, the layer factor.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

How much tensile load can 12G1.5 take, and how long can it hang freely?
The permissible pull force is 270 N. With a weight of about 430 kg/km this corresponds to a free-hanging vertical length of about 64 m before the rated pull is reached; apply your own safety factor for hoisting or suspended installations.

What is the voltage drop and heat loss of 12G1.5 at rated current?
At 12 A and a conductor temperature of 90 °C the voltage drop is about 40.7 V per 100 m and the conductor loss about 4.9 W per metre (maximum resistance 13.300 Ω/km at 20 °C).

Is this cable halogen-free?
No. The CPE rubber sheath contains halogen. If halogen-free cables are required, select the PUR version of the same construction.

Which cross-sections are available?
FC-MCR-R 12G: 0.75, 1, 1.5, 2.5, 4 mm². Other sizes and special designs can be produced to order.

Does this datasheet include mine-specific approvals?
No. Mine-specific approvals, such as coal-mine safety marks, MSHA or ATEX/IECEx for gassy atmospheres, depend on the project and the country and are not implied by this document. Send the requirements to FeiChun technical support.

13 Trademark Notice and Intellectual Property

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Mining and heavy industry: mining@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-MC062-2026-9715-EN
Revision 0 — first issue
Date 2 November 2026
Product FC-MCR-R 0.6/1 kV

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.