HARMONISED FLEXIBLE CABLE 450/750 V · DIN VDE 0282 / EN 50525 | 450/750 V | 16 sizes | CR rubber, low-temp | TINNED COPPER | LOW-TEMPERATURE GRADE

H07RN8-F 450/750 V

Submersible Rubber Cable 450/750 V 450/750 V – A single round core with a class 5 copper conductor, insulation and sheath. Low-temperature polychloroprene rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 16 sizes.

Document no. FC-TDS-VDE-2026-0821-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

H07RN8-F is the harmonised submersible rubber cable for 450/750 V. It is built like H07RN-F but with a water-resistant design that allows permanent immersion to a water depth of 10 m, which is why it is used for submersible pumps, fountains, dredging and drainage equipment.

Design

The conductors are class 5 fine-wire copper; the cores are insulated with EPR and stranded; multi-core cables from 7 cores and cables from 10 mm² carry a rubber inner sheath that keeps the core compact and water-resistant. The outer sheath is a polychloroprene compound qualified for permanent immersion. The cable corresponds to DIN VDE 0282 part 16 (HD 22.16).

Typical applications

- Submersible pumps in wells, shafts, sumps and dewatering applications
- Fountains, ponds and water features
- Dredging and underwater equipment with a feed cable
- Offshore and harbour installations at limited depth
- Construction-site dewatering and tunnel drainage
- Mine sump pumps and flooded workings
- Agricultural irrigation pumps
- Cold-climate duty: sites, cold stores and open-cast operations where the cable is moved at temperatures down to 40 °C

16 sizes	450/750 V	+60 °C	CR rubber, low-temp
Cross-section 1.5 – 300 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CR rubber, low-temp

Key features

- Permanent immersion to 10 m water depth
- Polychloroprene sheath with proven oil, weather and abrasion resistance
- EPR insulation, 60 °C at the conductor
- Rated voltage 450/750 V, test voltage 2.5 kV
- Class 5 conductors
- Flame-retardant to IEC 60332-1-2
- 16 sizes from 1.5 to 300 mm²; weight from 62 to 3,890 kg/km; copper from 14 to 2,880 kg/km

Core layout and conductor

A single round core with a class 5 copper conductor, insulation and sheath. In a three-phase circuit the three single-core cables are laid together. The conductors are tinned: each copper wire carries a thin tin coating. Tinning protects the copper against oxidation and corrosion in damp, salty or sulphurous atmospheres and keeps the conductor solderable, which is an advantage in outdoor, marine and mining installations. The resistance limits of tinned class 5 conductors are marginally higher than for bare copper; the R_{20} column shows the tinned values.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Standard background

DIN VDE 0282-16 (HD 22.16) specifies the harmonised H07RN8-F submersible rubber cable. The 8 in the designation stands for water-resistant construction. The cable must not be used where the water depth exceeds the rated depth, and the free cable end must always be kept above the water level or properly sealed.

The low-temperature grade of the sheath compound remains flexible down to 40 °C in motion and 50 °C in fixed installation, so the cable can be reeled and trailed on cold sites, in cold stores and in northern open-cast operations. The mechanical and electrical ratings are those of the standard grade; only the cold-flexing limit is extended.


450/750 V is the common rating for industrial and building-site distribution on 400 V systems and allows a margin for DC and rectified supplies. The test voltage is 2.5 kV.

02 Construction

FEICHUN · CROSS-SECTION A–A · 450/750 V

H07RN8-F

Sample size 1×35 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Tinned annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Insulation	EPR rubber, type EI4 (60 °C)
3	Outer sheath	Polychloroprene (CR) rubber, low-temperature grade

The drawing shows size 1×35. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

Construction details

Conductor	Tinned annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	EPR rubber, type EI4 (60 °C), maximum conductor temperature 60 °C
Core identification	Black to DIN VDE 0293-308
Stranding	Single core
Outer sheath	Polychloroprene (CR) rubber, low-temperature grade; thickness about 2.5 mm at this size

© 2026 Anhui FeiChun Special Cable Co., Ltd.

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	450/750 V AC
Test voltage	2.5 kV AC, 5 min
Maximum operating voltage, three-phase	825 V
Maximum operating voltage, DC (core-earth / core-core)	0.45/0.75 kV (DC 0.675/1.1 kV)
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, tinned

Thermal and mechanical data

Maximum conductor temperature	+60 °C
Maximum temperature at short circuit	+200 °C (5 s maximum)
Ambient temperature, fixed installation	−50 °C to +60 °C
Ambient temperature, in motion	−40 °C to +60 °C
Minimum bending radius	Fixed: 3 × D (D ≤ 12 mm), 4 × D (D > 12 mm); moving: 3 × D (D ≤ 8 mm), 4 × D (D ≤ 12 mm), 5 × D (D > 12 mm) (DIN VDE 0298-3)
Maximum tensile load	15 N/mm² continuous on the total copper cross-section
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CR rubber, low-temp)
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Permanent immersion to 10 m water depth

04 Dimensions, Weights and Rated Data – 450/750 V (16 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Outer Ø min mm	Outer Ø max mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
1×1.5	FC-H07R-0821-01	1.7	5.4	6.5	20	20	62	14	22	13.7	16	0.211
1×2.5	FC-H07R-0821-02	2.2	6.2	7.5	22	22	81	24	38	8.21	22	0.352
1×4	FC-H07R-0821-03	2.7	7.4	8.9	27	36	91	38	60	5.09	29	0.564
1×6	FC-H07R-0821-04	3.3	8.2	9.8	29	39	125	58	90	3.39	38	0.846
1×10	FC-H07R-0821-05	4.1	9.7	11.7	35	47	199	96	150	1.95	52	1.41
1×16	FC-H07R-0821-06	5.2	11.2	13.5	54	68	295	154	240	1.24	69	2.26
1×25	FC-H07R-0821-07	6.5	13.5	16.1	64	80	450	240	375	0.795	92	3.52
1×35	FC-H07R-0821-08	7.7	14.0	16.7	67	84	540	336	520	0.565	113	4.93
1×50	FC-H07R-0821-09	9.2	16.3	19.2	77	96	750	480	750	0.393	142	7.05
1×70	FC-H07R-0821-10	10.8	18.3	21.4	86	107	1,000	670	1,050	0.277	175	9.87
1×95	FC-H07R-0821-11	12.6	20.9	24.3	97	122	1,320	910	1,420	0.210	212	13.39
1×120	FC-H07R-0821-12	14.2	23.0	26.5	106	132	1,620	1,150	1,800	0.164	245	16.92
1×150	FC-H07R-0821-13	15.8	25.5	29.0	116	145	2,010	1,440	2,250	0.132	282	21.15
1×185	FC-H07R-0821-14	17.6	28.0	32.0	128	160	2,460	1,780	2,780	0.108	321	26.09
1×240	FC-H07R-0821-15	20.0	31.5	35.5	142	178	3,140	2,300	3,600	0.0817	378	33.84
1×300	FC-H07R-0821-16	22.4	35.0	39.0	156	195	3,890	2,880	4,500	0.0654	434	42.30

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores. Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Ambient temperature factors (conductor 60 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.15	1.08	1.00	0.91	0.82	0.71	0.58	0.41	–

Short-circuit current rating

I_k = 0.141 kA/mm² × cross-section of the power core (conductor 60 °C → 200 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 60 °C, cos φ = 0.8 and reactance 0.08 Ω/km (single-phase AC, round trip). The percentage refers to a system voltage of 400 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 60 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 400 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
1×1.5	16	15.9	40.74	10.18	0.81	0.669	0.299	0.211	0.122
1×2.5	22	9.50	33.65	8.41	0.92	1.11	0.499	0.352	0.204
1×4	29	5.89	27.61	6.90	0.99	1.78	0.798	0.564	0.326
1×6	38	3.92	24.22	6.05	1.13	2.68	1.20	0.846	0.488
1×10	52	2.26	19.27	4.82	1.22	4.46	1.99	1.41	0.814
1×16	69	1.43	16.50	4.13	1.37	7.13	3.19	2.26	1.30
1×25	92	0.920	14.43	3.61	1.56	11.15	4.99	3.52	2.04
1×35	113	0.654	12.91	3.23	1.67	15.61	6.98	4.93	2.85
1×50	142	0.455	11.70	2.92	1.83	22.29	9.97	7.05	4.07
1×70	175	0.321	10.66	2.66	1.96	31.21	13.96	9.87	5.70
1×95	212	0.243	10.28	2.57	2.18	42.36	18.94	13.39	7.73
1×120	245	0.190	9.79	2.45	2.28	53.51	23.93	16.92	9.77
1×150	282	0.153	9.60	2.40	2.43	66.88	29.91	21.15	12.21
1×185	321	0.125	9.50	2.38	2.58	82.49	36.89	26.09	15.06
1×240	378	0.0945	9.35	2.34	2.70	107.01	47.86	33.84	19.54
1×300	434	0.0757	9.42	2.36	2.85	133.76	59.82	42.30	24.42

06 Selection Guide and Sizing Aid

H07RN8-F covers 16 sizes. The smallest, 1×1.5, has an outer diameter of up to 6.5 mm and weighs about 62 kg/km; the largest, 1×300, has an outer diameter of up to 39.0 mm and weighs about 3,890 kg/km, 62.7 times as much. Across the range the rated current rises from 16 A to 434 A at 30 °C and the fixed bending radius from 20 mm to 156 mm.

Example 1. A circuit draws 41 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.82, grouping factor 0.80: required table current = 41 / (0.82 × 0.80) = 63 A. The smallest suitable size is 1×16 with 69 A.

Example 2. A circuit draws 178 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.91: required table current = 178 / (0.91) = 195 A. The smallest suitable size is 1×95 with 212 A.

07 Engineering Profile by Size

Every size of H07RN8-F with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

1×1.5. This size has with a conductor of Ø 1.7 mm under 0.80 mm of insulation (core Ø 3.3 mm) and an outer sheath of 1.3 mm; outer diameter 5.4–6.5 mm, weight about 62 kg/km of which copper 14 kg/km (23 %). Rated current 16 A at 30 °C; at that load the voltage drop is 40.74 V per 100 m (10.18 % of 400 V) and the loss 0.81 kW per 100 m. Bending radius 20 mm fixed, 20 mm moving; gland M16, lug bolt M5. Short-circuit rating 0.211 kA for 1 s; permitted pull 22 N, free-hanging length 36 m.

1×2.5. This size has with a conductor of Ø 2.1 mm under 0.90 mm of insulation (core Ø 3.9 mm) and an outer sheath of 1.5 mm; outer diameter 6.2–7.5 mm, weight about 81 kg/km of which copper 24 kg/km (30 %). Rated current 22 A at 30 °C; at that load the voltage drop is 33.65 V per 100 m (8.41 % of 400 V) and the loss 0.92 kW per 100 m. Bending radius 22 mm fixed, 22 mm moving; gland M16, lug bolt M5. Short-circuit rating 0.352 kA for 1 s; permitted pull 38 N, free-hanging length 47 m.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

1×4. This size has with a conductor of Ø 2.7 mm under 1.00 mm of insulation (core Ø 4.7 mm) and an outer sheath of 1.7 mm; outer diameter 7.4–8.9 mm, weight about 91 kg/km of which copper 38 kg/km (42 %). Rated current 29 A at 30 °C; at that load the voltage drop is 27.61 V per 100 m (6.90 % of 400 V) and the loss 0.99 kW per 100 m. Bending radius 27 mm fixed, 36 mm moving; gland M16, lug bolt M5. Short-circuit rating 0.564 kA for 1 s; permitted pull 60 N, free-hanging length 67 m.

1×6. This size has with a conductor of Ø 3.3 mm under 1.00 mm of insulation (core Ø 5.3 mm) and an outer sheath of 1.9 mm; outer diameter 8.2–9.8 mm, weight about 125 kg/km of which copper 58 kg/km (46 %). Rated current 38 A at 30 °C; at that load the voltage drop is 24.22 V per 100 m (6.05 % of 400 V) and the loss 1.13 kW per 100 m. Bending radius 29 mm fixed, 39 mm moving; gland M16, lug bolt M5. Short-circuit rating 0.846 kA for 1 s; permitted pull 90 N, free-hanging length 73 m.

1×10. This size has with a conductor of Ø 4.1 mm under 1.20 mm of insulation (core Ø 6.5 mm) and an outer sheath of 2.1 mm; outer diameter 9.7–11.7 mm, weight about 199 kg/km of which copper 96 kg/km (48 %). Rated current 52 A at 30 °C; at that load the voltage drop is 19.27 V per 100 m (4.82 % of 400 V) and the loss 1.22 kW per 100 m. Bending radius 35 mm fixed, 47 mm moving; gland M20, lug bolt M6. Short-circuit rating 1.41 kA for 1 s; permitted pull 150 N, free-hanging length 76 m.

1×16. This size has with a conductor of Ø 5.2 mm under 1.20 mm of insulation (core Ø 7.6 mm) and an outer sheath of 2.4 mm; outer diameter 11.2–13.5 mm, weight about 295 kg/km of which copper 154 kg/km (52 %). Rated current 69 A at 30 °C; at that load the voltage drop is 16.50 V per 100 m (4.13 % of 400 V) and the loss 1.37 kW per 100 m. Bending radius 54 mm fixed, 68 mm moving; gland M25, lug bolt M6. Short-circuit rating 2.26 kA for 1 s; permitted pull 240 N, free-hanging length 82 m.

1×25. This size has with a conductor of Ø 6.5 mm under 1.40 mm of insulation (core Ø 9.3 mm) and an outer sheath of 2.8 mm; outer diameter 13.5–16.1 mm, weight about 450 kg/km of which copper 240 kg/km (53 %). Rated current 92 A at 30 °C; at that load the voltage drop is 14.43 V per 100 m (3.61 % of 400 V) and the loss 1.56 kW per 100 m. Bending radius 64 mm fixed, 80 mm moving; gland M25, lug bolt M8. Short-circuit rating 3.52 kA for 1 s; permitted pull 375 N, free-hanging length 84 m.

1×35. This size has with a conductor of Ø 7.6 mm under 1.40 mm of insulation (core Ø 10.4 mm) and an outer sheath of 2.5 mm; outer diameter 14.0–16.7 mm, weight about 540 kg/km of which copper 336 kg/km (62 %). Rated current 113 A at 30 °C; at that load the voltage drop is 12.91 V per 100 m (3.23 % of 400 V) and the loss 1.67 kW per 100 m. Bending radius 67 mm fixed, 84 mm moving; gland M25, lug bolt M8. Short-circuit rating 4.93 kA for 1 s; permitted pull 520 N, free-hanging length 98 m.

1×50. This size has with a conductor of Ø 9.1 mm under 1.60 mm of insulation (core Ø 12.3 mm) and an outer sheath of 2.7 mm; outer diameter 16.3–19.2 mm, weight about 750 kg/km of which copper 480 kg/km (64 %). Rated current 142 A at 30 °C; at that load the voltage drop is 11.70 V per 100 m (2.92 % of 400 V) and the loss 1.83 kW per 100 m. Bending radius 77 mm fixed, 96 mm moving; gland M32, lug bolt M10. Short-circuit rating 7.05 kA for 1 s; permitted pull 750 N, free-hanging length 101 m.

1×70. This size has with a conductor of Ø 10.8 mm under 1.60 mm of insulation (core Ø 14.0 mm) and an outer sheath of 2.9 mm; outer diameter 18.3–21.4 mm, weight about 1,000 kg/km of which copper 670 kg/km (67 %). Rated current 175 A at 30 °C; at that load the voltage drop is 10.66 V per 100 m (2.66 % of 400 V) and the loss 1.96 kW per 100 m. Bending radius 86 mm fixed, 107 mm moving; gland M32, lug bolt M10. Short-circuit rating 9.87 kA for 1 s; permitted pull 1,050 N, free-hanging length 107 m.

1×95. This size has with a conductor of Ø 12.6 mm under 1.80 mm of insulation (core Ø 16.2 mm) and an outer sheath of 3.2 mm; outer diameter 20.9–24.3 mm, weight about 1,320 kg/km of which copper 910 kg/km (69 %). Rated current 212 A at 30 °C; at that load the voltage drop is 10.28 V per 100 m (2.57 % of 400 V) and the loss 2.18 kW per 100 m. Bending radius 97 mm fixed, 122 mm moving; gland M32, lug bolt M12. Short-circuit rating 13.39 kA for 1 s; permitted pull 1,420 N, free-hanging length 109 m.

1×120. This size has with a conductor of Ø 14.1 mm under 1.80 mm of insulation (core Ø 17.7 mm) and an outer sheath of 3.4 mm; outer diameter 23.0–26.5 mm, weight about 1,620 kg/km of which copper 1,150 kg/km (71 %). Rated current 245 A at 30 °C; at that load the voltage drop is 9.79 V per 100 m (2.45 % of 400 V) and the loss 2.28 kW per 100 m. Bending radius 106 mm fixed, 132 mm moving; gland M40, lug bolt M12. Short-circuit rating 16.92 kA for 1 s; permitted pull 1,800 N, free-hanging length 113 m.

1×150. This size has with a conductor of Ø 15.8 mm under 2.00 mm of insulation (core Ø 19.8 mm) and an outer sheath of 3.7 mm; outer diameter 25.5–29.0 mm, weight about 2,010 kg/km of which copper 1,440 kg/km (72 %). Rated current 282 A at 30 °C; at that load the voltage drop is 9.60 V per 100 m (2.40 % of 400 V) and the loss 2.43 kW per 100 m. Bending radius 116 mm fixed, 145 mm moving; gland M40, lug bolt M12. Short-circuit rating 21.15 kA for 1 s; permitted pull 2,250 N, free-hanging length 114 m.

1×185. This size has with a conductor of Ø 17.5 mm under 2.20 mm of insulation (core Ø 21.9 mm) and an outer sheath of 4.0 mm; outer diameter 28.0–32.0 mm, weight about 2,460 kg/km of which copper 1,780 kg/km (72 %). Rated current 321 A at 30 °C; at that load the voltage drop is 9.50 V per 100 m (2.38 % of 400 V) and the loss 2.58 kW

© 2026 Anhui FeiChun Special Cable Co., Ltd.

per 100 m. Bending radius 128 mm fixed, 160 mm moving; gland M40, lug bolt M16. Short-circuit rating 26.09 kA for 1 s; permitted pull 2,780 N, free-hanging length 115 m.

1×240. This size has with a conductor of Ø 20.0 mm under 2.40 mm of insulation (core Ø 24.8 mm) and an outer sheath of 4.3 mm; outer diameter 31.5–35.5 mm, weight about 3,140 kg/km of which copper 2,300 kg/km (73 %). Rated current 378 A at 30 °C; at that load the voltage drop is 9.35 V per 100 m (2.34 % of 400 V) and the loss 2.70 kW per 100 m. Bending radius 142 mm fixed, 178 mm moving; gland M50, lug bolt M16. Short-circuit rating 33.84 kA for 1 s; permitted pull 3,600 N, free-hanging length 116 m.

1×300. This size has with a conductor of Ø 22.3 mm under 2.60 mm of insulation (core Ø 27.5 mm) and an outer sheath of 4.7 mm; outer diameter 35.0–39.0 mm, weight about 3,890 kg/km of which copper 2,880 kg/km (74 %). Rated current 434 A at 30 °C; at that load the voltage drop is 9.42 V per 100 m (2.36 % of 400 V) and the loss 2.85 kW per 100 m. Bending radius 156 mm fixed, 195 mm moving; gland M63, lug bolt M16. Short-circuit rating 42.30 kA for 1 s; permitted pull 4,500 N, free-hanging length 117 m.

Averaged over all sizes copper makes up 70 % of the cable weight; the share rises from 23 % at 1×1.5 to 74 % at 1×300, which is why the larger sizes are costed mostly on the copper market price.

08 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 450/750 V.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Laid-up core Ø mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
1×1.5	1.65	3.25	0.80	3.3	–	1.35	–	45
1×2.5	2.13	3.93	0.90	3.9	–	1.46	–	43
1×4	2.70	4.70	1.00	4.7	–	1.71	–	42
1×6	3.30	5.30	1.00	5.3	–	1.85	–	41
1×10	4.08	6.48	1.20	6.5	–	2.11	–	39
1×16	5.16	7.56	1.20	7.6	–	2.38	–	39
1×25	6.45	9.25	1.40	9.3	–	2.77	–	37
1×35	7.63	10.43	1.40	10.4	–	2.46	–	32
1×50	9.12	12.32	1.60	12.3	–	2.71	–	31
1×70	10.79	13.99	1.60	14.0	–	2.93	–	29
1×95	12.57	16.17	1.80	16.2	–	3.21	–	28
1×120	14.13	17.73	1.80	17.7	–	3.42	–	28
1×150	15.80	19.80	2.00	19.8	–	3.69	–	27
1×185	17.55	21.95	2.20	21.9	–	3.97	–	27
1×240	19.99	24.79	2.40	24.8	–	4.34	–	26
1×300	22.35	27.55	2.60	27.5	–	4.70	–	25

© 2026 Anhui FeiChun Special Cable Co., Ltd.

09 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
1×1.5	6.5	M16	M5	10	10
1×2.5	7.5	M16	M5	10	10
1×4	8.9	M16	M5	10	15
1×6	9.8	M16	M5	11	15
1×10	11.7	M20	M6	11	20
1×16	13.5	M25	M6	12	25
1×25	16.1	M25	M8	14	30
1×35	16.7	M25	M8	16	35
1×50	19.2	M32	M10	19	40
1×70	21.4	M32	M10	26	45
1×95	24.3	M32	M12	31	50
1×120	26.5	M40	M12	35	55
1×150	29.0	M40	M12	41	60
1×185	32.0	M40	M16	47	65
1×240	35.5	M50	M16	57	70
1×300	39.0	M63	M16	57	80

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

10 Comparison with Related Variants at Size 1×35

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet H07RN8-F 450/750 V	–	16.7	540	520	113
H07RN8-F 2× 450/750 V 2×16	core configuration	24.3 (+46%)	710 (+31%)	480 (-8%)	69 (-39%)
H07RN8-F 3× 450/750 V 3×35	core configuration	32.5 (+95%)	1,790 (+231%)	1,580 (+204%)	113 (+0%)
H07RN8-F 450/750 V 1×35	tinned vs bare copper	16.7 (+0%)	540 (+0%)	520 (+0%)	114 (+1%)
H07RN8-F 450/750 V 1×35	low-temperature sheath	16.7 (+0%)	540 (+0%)	520 (+0%)	113 (+0%)
H07RN8-F 3G 450/750 V 3G35	core configuration	32.5 (+95%)	1,790 (+231%)	1,580 (+204%)	113 (+0%)
H07RN8-F 4× 450/750 V 4×35	core configuration	36.5 (+119%)	2,370 (+339%)	2,100 (+304%)	96 (-15%)
H07RN8-F 4G 450/750 V 4G35	core configuration	36.5 (+119%)	2,370 (+339%)	2,100 (+304%)	113 (+0%)
H07RN8-F 5× 450/750 V 5×35	core configuration	40.0 (+140%)	2,850 (+428%)	2,620 (+404%)	85 (-25%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

11 Standards and Testing

Standard	Scope
DIN VDE 0282-16 (HD 22.16)	Submersible flexible rubber cables H07RN8-F
DIN VDE 0293-308	Core identification
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN VDE 0298-3 / -4	Application and current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation

Routine and type tests

- AC voltage test on every drum length (routine test): 2.5 kV, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors
- Flame propagation test (IEC 60332-1-2) and mineral-oil resistance on type-test samples

Test documentation: every delivery is accompanied by a test certificate from FeiChun's own laboratory. Third-party witnessed tests can be arranged at the buyer's cost.

The design follows DIN VDE 0282-16. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

12 Installation, Marking and Delivery

Installation guidance

- Never terminate the cable under water; keep the cable end above the water level or seal it in a watertight enclosure.
- Hang heavy pumps on a separate rope, never by the cable.
- Respect the water depth rating of 10 m.
- Seal the cable entry of the pump with a gland that matches the maximum outer diameter.
- Inspect the sheath regularly for cuts and abrasion at the water line.
- Do not exceed the tensile load of 15 N/mm² of the copper cross-section.

Sheath marking

FEICHUN H07RN8-F [cross-section] 450/750 V [year] [serial no.] [metre mark]

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: H07RN8-F 1×35 450/750 V – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (tinned), length per piece, required standards and installation conditions.

13 Certification and Quality

All cable is subject to FeiChun's quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

14 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- H07RN8-F 2× 450/750 V – core configuration, CR rubber, low-temp, tinned
- H07RN8-F 3× 450/750 V – core configuration, CR rubber, low-temp, tinned
- H07RN8-F 450/750 V – tinned vs bare copper, CR rubber, low-temp
- H07RN8-F 450/750 V – low-temperature sheath, CR rubber, tinned

© 2026 Anhui FeiChun Special Cable Co., Ltd.

- H07RN8-F 3G 450/750 V – core configuration, CR rubber, low-temp, tinned
- H07RN8-F 4× 450/750 V – core configuration, CR rubber, low-temp, tinned
- H07RN8-F 4G 450/750 V – core configuration, CR rubber, low-temp, tinned
- H07RN8-F 5× 450/750 V – core configuration, CR rubber, low-temp, tinned

Overview of all H07RN8-F datasheets: H07 Series Flexible Cables 450/750 V

Frequently asked questions

How deep can H07RN8-F be submerged?
To a water depth of 10 m, continuously.

What is the difference to H07RN-F?
H07RN8-F has a design that is qualified for permanent immersion; H07RN-F is designed for water spray and temporary immersion only.

What sizes are available for H07RN8-F?
16 sizes from 1.5 to 300 mm². The outer dimension of the largest size, 1×300, is 39.0 mm and the weight is about 3,890 kg/km.

What current can 1×50 carry?
142 A in free air at 30 °C ambient, with the conductor at 60 °C. Other temperatures and grouping change the value; use the factors in section 04.

15 Trademark Notice and Intellectual Property

Cable type designations such as H07RN8-F are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0821-EN
Revision 0 — first issue
Date 2 November 2026
Product H07RN8-F 450/750 V

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.