HARMONISED FLEXIBLE CABLE 450/750 V · DIN VDE 0282 / EN 50525 | 450/750 V | 7 sizes | halogen-free FRNC, low-temp | TINNED COPPER | LOW-TEMPERATURE GRADE

H07ZZ-F 2× 450/750 V

Halogen-Free Flexible Cable 450/750 V 450/750 V – 2 cores of equal cross-section in concentric layers with a short lay length. Low-temperature halogen-free FRNC sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 7 sizes.

Document no. FC-TDS-VDE-2026-0930-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

H07ZZ-F is the harmonised halogen-free flexible cable for 450/750 V. Cross-linked halogen-free insulation and a halogen-free flame-retardant sheath give a flexible, oil-resistant cable that does not release halogen acids in a fire, for installations where people or equipment must be protected.

Design

The conductors are class 5 fine-wire copper, bare or tinned. The cores are insulated with a cross-linked halogen-free compound for 90 °C at the conductor. The sheath is a halogen-free flame-retardant elastomer; multi-core cables from 7 cores and cables from 10 mm² carry an inner sheath. The type is covered by DIN EN 50525-3-21.

Typical applications

- Exhibition halls, theatres and venues with high safety requirements
- Public transport, tunnels and underground installations
- Data centres, control rooms and clean production areas
- Ships and offshore installations where halogen-free cables are specified
- Mobile power distribution for events in enclosed buildings
- Machine connections in plants with halogen-free requirements
- Cable for hospitals, airports and schools
- Cold-climate duty: sites, cold stores and open-cast operations where the cable is moved at temperatures down to 40 °C

7 sizes	450/750 V	+90 °C	Halogen-free
Cross-section 1 – 16 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: halogen-free FRNC, low-temp

Key features

- Halogen-free insulation and sheath (IEC 60754-1/-2)
- Rated 90 °C at the conductor; short-circuit temperature 250 °C
- Rated voltage 450/750 V, test voltage 2.5 kV
- Class 5 conductors for flexible use
- Flame-retardant to IEC 60332-1-2; low smoke development
- Oil-resistant sheath
- 7 sizes from 1 to 16 mm²; weight from 93 to 700 kg/km; copper from 19 to 307 kg/km

Core layout and conductor

2 cores of equal cross-section in concentric layers with a short lay length. Core colours: brown, blue (DIN VDE 0293-308); no protective core is included. Two-core cables serve single-phase AC and DC supplies. The conductors are tinned: each copper wire carries a thin tin coating. Tinning protects the copper against oxidation and corrosion in damp, salty or sulphurous atmospheres and keeps the conductor solderable, which is an advantage in outdoor, marine and mining installations. The resistance limits of tinned class 5 conductors are marginally higher than for bare copper; the R_{20} column shows the tinned values.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Standard background

H07ZZ-F and H05ZZ-F are harmonised halogen-free types covered by DIN EN 50525-3-21 (VDE 0285-525-3-21). ZZ identifies the thermoset halogen-free insulation and sheath.

The low-temperature grade of the sheath compound remains flexible down to 40 °C in motion and 50 °C in fixed installation, so the cable can be reeled and trailed on cold sites, in cold stores and in northern open-cast operations. The mechanical and electrical ratings are those of the standard grade; only the cold-flexing limit is extended.


450/750 V is the common rating for industrial and building-site distribution on 400 V systems and allows a margin for DC and rectified supplies. The test voltage is 2.5 kV.

02 Construction

FEICHUN · CROSS-SECTION A–A · 450/750 V

H07ZZ-F

Sample size 2×4 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Tinned annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Insulation	Halogen-free cross-linked compound, type HX
3	Filler and binder tape	Halogen-free filler with polyester binder tape
4	Outer sheath	Halogen-free flame-retardant elastomer, low-temperature grade

The drawing shows size 2×4. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

Construction details

Conductor	Tinned annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	Halogen-free cross-linked compound, type HX, maximum conductor temperature 90 °C
Core identification	Brown, blue to DIN VDE 0293-308
Stranding	Cores in concentric layers with a short lay length
Outer sheath	Halogen-free flame-retardant elastomer, low-temperature grade; thickness about 1.7 mm at this size

© 2026 Anhui FeiChun Special Cable Co., Ltd.

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	450/750 V AC
Test voltage	2.5 kV AC, 5 min
Maximum operating voltage, three-phase	825 V
Maximum operating voltage, DC (core-earth / core-core)	0.45/0.75 kV (DC 0.675/1.1 kV)
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, tinned

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C (5 s maximum)
Ambient temperature, fixed installation	−50 °C to +90 °C
Ambient temperature, in motion	−40 °C to +90 °C
Minimum bending radius	Fixed: 3 × D (D ≤ 12 mm), 4 × D (D > 12 mm); moving: 3 × D (D ≤ 8 mm), 4 × D (D ≤ 12 mm), 5 × D (D > 12 mm) (DIN VDE 0298-3)
Maximum tensile load	15 N/mm² continuous on the total copper cross-section
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	Yes (insulation and sheath), IEC 60754-1/-2
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Damp and wet areas, spray water

04 Dimensions, Weights and Rated Data – 450/750 V (7 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Outer Ø min mm	Outer Ø max mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
2×1	FC-H07Z-0930-01	1.4	7.7	9.2	28	37	93	19	30	20.0	17	0.143
2×1.5	FC-H07Z-0930-02	1.7	8.6	10.4	31	42	121	29	45	13.7	22	0.214
2×2.5	FC-H07Z-0930-03	2.2	10.1	12.2	49	61	164	48	75	8.21	31	0.357
2×4	FC-H07Z-0930-04	2.7	12.2	14.6	58	73	188	77	120	5.09	41	0.572
2×6	FC-H07Z-0930-05	3.3	13.7	16.3	65	82	262	115	180	3.39	53	0.858
2×10	FC-H07Z-0930-06	4.1	18.1	21.2	85	106	470	192	300	1.95	73	1.43
2×16	FC-H07Z-0930-07	5.2	20.9	24.3	97	122	700	307	480	1.24	98	2.29

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores. Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.71

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

© 2026 Anhui FeiChun Special Cable Co., Ltd.

05 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 90 °C, cos φ = 0.8 and reactance 0.08 Ω/km (three-phase). The percentage refers to a system voltage of 400 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 90 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 400 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
2×1	17	25.5	60.21	15.05	2.21	0.452	0.202	0.143	0.083
2×1.5	22	17.5	53.44	13.36	2.54	0.678	0.303	0.214	0.124
2×2.5	31	10.5	45.23	11.31	3.02	1.13	0.506	0.357	0.206
2×4	41	6.49	37.21	9.30	3.27	1.81	0.809	0.572	0.330
2×6	53	4.32	32.19	8.05	3.64	2.71	1.21	0.858	0.495
2×10	73	2.49	25.76	6.44	3.98	4.52	2.02	1.43	0.826
2×16	98	1.58	22.29	5.57	4.56	7.24	3.24	2.29	1.32

06 Selection Guide and Sizing Aid

H07ZZ-F 2× covers 7 sizes. The smallest, 2×1, has an outer diameter of up to 9.2 mm and weighs about 93 kg/km; the largest, 2×16, has an outer diameter of up to 24.3 mm and weighs about 700 kg/km, 7.5 times as much. Across the range the rated current rises from 17 A to 98 A at 30 °C and the fixed bending radius from 28 mm to 97 mm.

Example 1. A circuit draws 21 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.91, grouping factor 0.80: required table current = 21 / (0.91 × 0.80) = 29 A. The smallest suitable size is 2×2.5 with 31 A.

Example 2. A circuit draws 47 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.96: required table current = 47 / (0.96) = 50 A. The smallest suitable size is 2×6 with 53 A.

07 Engineering Profile by Size

Every size of H07ZZ-F 2× with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

2×1. This size has with a conductor of Ø 1.3 mm under 0.70 mm of insulation (core Ø 2.7 mm) and an outer sheath of 1.2 mm; outer diameter 7.7–9.2 mm, weight about 93 kg/km of which copper 19 kg/km (20 %). Rated current 17 A at 30 °C; at that load the voltage drop is 60.21 V per 100 m (15.05 % of 400 V) and the loss 2.21 kW per 100 m. Bending radius 28 mm fixed, 37 mm moving; gland M16, lug bolt M5. Short-circuit rating 0.143 kA for 1 s; permitted pull 30 N, free-hanging length 32 m.

2×1.5. This size has with a conductor of Ø 1.7 mm under 0.80 mm of insulation (core Ø 3.3 mm) and an outer sheath of 1.2 mm; outer diameter 8.6–10.4 mm, weight about 121 kg/km of which copper 29 kg/km (24 %). Rated current 22 A at 30 °C; at that load the voltage drop is 53.44 V per 100 m (13.36 % of 400 V) and the loss 2.54 kW per 100 m. Bending radius 31 mm fixed, 42 mm moving; gland M20, lug bolt M5. Short-circuit rating 0.214 kA for 1 s; permitted pull 45 N, free-hanging length 37 m.

2×2.5. This size has with a conductor of Ø 2.1 mm under 0.90 mm of insulation (core Ø 3.9 mm) and an outer sheath of 1.3 mm; outer diameter 10.1–12.2 mm, weight about 164 kg/km of which copper 48 kg/km (29 %). Rated current 31 A at 30 °C; at that load the voltage drop is 45.23 V per 100 m (11.31 % of 400 V) and the loss 3.02 kW per 100 m. Bending radius 49 mm fixed, 61 mm moving; gland M25, lug bolt M5. Short-circuit rating 0.357 kA for 1 s; permitted pull 75 N, free-hanging length 46 m.

2×4. This size has with a conductor of Ø 2.7 mm under 1.00 mm of insulation (core Ø 4.7 mm) and an outer sheath of 1.7 mm; outer diameter 12.2–14.6 mm, weight about 188 kg/km of which copper 77 kg/km (41 %). Rated current 41 A at 30 °C; at that load the voltage drop is 37.21 V per 100 m (9.30 % of 400 V) and the loss 3.27 kW per 100 m. Bending radius 58 mm fixed, 73 mm moving; gland M25, lug bolt M5. Short-circuit rating 0.572 kA for 1 s; permitted pull 120 N, free-hanging length 65 m.

2×6. This size has with a conductor of Ø 3.3 mm under 1.00 mm of insulation (core Ø 5.3 mm) and an outer sheath of 1.9 mm; outer diameter 13.7–16.3 mm, weight about 262 kg/km of which copper 115 kg/km (44 %). Rated current 53 A at 30 °C; at that load the voltage drop is 32.19 V per 100 m (8.05 % of 400 V) and the loss 3.64 kW per 100 m. Bending radius 65 mm fixed, 82 mm moving; gland M25, lug bolt M5. Short-circuit rating 0.858 kA for 1 s; permitted pull 180 N, free-hanging length 70 m.

2×10. This size has with a conductor of Ø 4.1 mm under 1.20 mm of insulation (core Ø 6.5 mm) and 0.8 mm inner and 2.3 mm outer sheath; outer diameter 18.1–21.2 mm, weight about 470 kg/km of which copper 192 kg/km (41 %). Rated current 73 A at 30 °C; at that load the voltage drop is 25.76 V per 100 m (6.44 % of 400 V) and the loss 3.98 kW

© 2026 Anhui FeiChun Special Cable Co., Ltd.

per 100 m. Bending radius 85 mm fixed, 106 mm moving; gland M32, lug bolt M6. Short-circuit rating 1.43 kA for 1 s; permitted pull 300 N, free-hanging length 65 m.

2×16. This size has with a conductor of Ø 5.2 mm under 1.20 mm of insulation (core Ø 7.6 mm) and 0.8 mm inner and 2.6 mm outer sheath; outer diameter 20.9–24.3 mm, weight about 700 kg/km of which copper 307 kg/km (44 %). Rated current 98 A at 30 °C; at that load the voltage drop is 22.29 V per 100 m (5.57 % of 400 V) and the loss 4.56 kW per 100 m. Bending radius 97 mm fixed, 122 mm moving; gland M32, lug bolt M6. Short-circuit rating 2.29 kA for 1 s; permitted pull 480 N, free-hanging length 69 m.

Averaged over all sizes copper makes up 39 % of the cable weight; the share rises from 20 % at 2×1 to 44 % at 2×16, which is why the larger sizes are costed mostly on the copper market price.

08 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 450/750 V.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Laid-up core Ø mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
2×1	1.35	2.75	0.70	6.1	–	1.17	–	28
2×1.5	1.65	3.25	0.80	7.1	–	1.21	–	25
2×2.5	2.13	3.93	0.90	8.5	–	1.33	–	24
2×4	2.70	4.70	1.00	10.0	–	1.69	–	25
2×6	3.30	5.30	1.00	11.2	–	1.88	–	25
2×10	4.08	6.48	1.20	13.6	0.77	2.25	–	31
2×16	5.16	7.56	1.20	15.7	0.80	2.63	–	30

09 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
2×1	9.2	M16	M5	10	15
2×1.5	10.4	M20	M5	10	15
2×2.5	12.2	M25	M5	10	25
2×4	14.6	M25	M5	10	30
2×6	16.3	M25	M5	11	30
2×10	21.2	M32	M6	11	40
2×16	24.3	M32	M6	12	50

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

10 Comparison with Related Variants at Size 2×4

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet H07ZZ-F 2× 450/750 V	–	14.6	188	120	41
H07ZZ-F 450/750 V 1×4	core configuration	8.9 (-39%)	89 (-53%)	60 (-50%)	41 (+0%)
H07ZZ-F 3× 450/750 V 3×4	core configuration	15.7 (+8%)	262 (+39%)	180 (+50%)	41 (+0%)
H07ZZ-F 2× 450/750 V 2×4	tinned vs bare copper	14.6 (+0%)	188 (+0%)	120 (+0%)	42 (+2%)
H07ZZ-F 2× 450/750 V 2×4	low-temperature sheath	14.6 (+0%)	188 (+0%)	120 (+0%)	41 (+0%)
H07ZZ-F 3G 450/750 V 3G4	core configuration	15.7 (+8%)	262 (+39%)	180 (+50%)	41 (+0%)
H07ZZ-F 4× 450/750 V 4×4	core configuration	17.5 (+20%)	344 (+83%)	240 (+100%)	35 (-15%)
H07ZZ-F 4G 450/750 V 4G4	core configuration	17.5 (+20%)	344 (+83%)	240 (+100%)	41 (+0%)
H07ZZ-F 5× 450/750 V 5×4	core configuration	19.0 (+30%)	410 (+118%)	300 (+150%)	31 (-24%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

11 Standards and Testing

Standard	Scope
DIN EN 50525-3-21 (VDE 0285-525-3-21)	Halogen-free thermoset flexible cables
IEC 60754-1 / -2	Halogen content and acidity
DIN VDE 0293-308	Core identification
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation

Routine and type tests

- AC voltage test on every drum length (routine test): 2.5 kV, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors
- Flame propagation test (IEC 60332-1-2) on type-test samples
- Verification of the halogen-free compounds (IEC 60754-1/-2)

Test documentation: every delivery is accompanied by a test certificate from FeiChun’s own laboratory. Third-party witnessed tests can be arranged at the buyer’s cost.

The design follows DIN EN 50525-3-21. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

12 Installation, Marking and Delivery

Installation guidance

- Observe the bending radii in section 04.
- Do not exceed the tensile load of 15 N/mm² of the copper cross-section.
- Select halogen-free glands and fittings to maintain the halogen-free concept of the installation.
- Do not use below the rated minimum temperature when moving the cable.
- Unwind from the drum completely before applying full load.
- Protect the sheath from permanent abrasion.

Sheath marking

FEICHUN H07ZZ-F [cross-section] 450/750 V [year] [serial no.] [metre mark]

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: H07ZZ-F 2×4 450/750 V – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (tinned), length per piece, required standards and installation conditions.

13 Certification and Quality

All cable is subject to FeiChun’s quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

14 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- H07ZZ-F 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned
- H07ZZ-F 3× 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned
- H07ZZ-F 2× 450/750 V – tinned vs bare copper, halogen-free FRNC, low-temp
- H07ZZ-F 2× 450/750 V – low-temperature sheath, halogen-free FRNC, tinned
- H07ZZ-F 3G 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned
- H07ZZ-F 4× 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned
- H07ZZ-F 4G 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned
- H07ZZ-F 5× 450/750 V – core configuration, halogen-free FRNC, low-temp, tinned

Overview of all H07ZZ-F datasheets: H07 Series Flexible Cables 450/750 V

Frequently asked questions

What does ZZ mean in H07ZZ-F?
Halogen-free thermoset insulation (Z) and halogen-free thermoset sheath (Z); F means flexible conductors.

Is H07ZZ-F suitable for outdoor use?
Yes, within the temperature range; for permanent outdoor exposure check the sheath for UV and weather suitability.

What sizes are available for H07ZZ-F 2×?
7 sizes from 1 to 16 mm². The outer dimension of the largest size, 2×16, is 24.3 mm and the weight is about 700 kg/km.

What current can 2×4 carry?
41 A in free air at 30 °C ambient, with the conductor at 90 °C. Other temperatures and grouping change the value; use the factors in section 04.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

15 Trademark Notice and Intellectual Property

Cable type designations such as H07ZZ-F are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0930-EN
Revision 0 — first issue
Date 2 November 2026
Product H07ZZ-F 450/750 V

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.