DIN VDE 0250-813 · MV TRAILING AND REELING CABLE | 3.6/6 kV | 8 sizes | CR rubber | BARE COPPER | TENSILE SUPPORT BRAID

(N)TSCGEWöu-C-HT 3×+3E+2×1.5

3.6/6 kV

Medium-Voltage Trailing and Reeling Cable 3.6/6 kV – 3 screened power cores + 3 split PE conductors + 2 control cores. Polychloroprene rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 8 sizes.

Document no. FC-TDS-VDE-2026-0452-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

(N)TSCGEWöu-C-HT is a medium-voltage trailing cable to DIN VDE 0250-813 for mobile equipment that is supplied from a drag cable or a cable reel. Three individually screened, EPR-insulated power cores and three split protective conductors are stranded together, bedded in a rubber inner sheath and covered with an oil-resistant polychloroprene outer sheath. The cable is used for 3.6/6 kV supply of excavators, shovels, crushers and reclaimers.

Design

Each power core has an inner and an outer semi-conductive layer extruded together with the EPR insulation and a tinned or bare copper-wire braid screen. This keeps the electric field inside the core insulation and lets the cores be terminated with standard medium-voltage accessories. The three protective conductors lie in the outer interstices and carry the earth current; their total cross-section is stated in the designation (for example 3×50+3×25/3E means three conductors of 50 mm² and three protective conductors of 25 mm² in total). The inner and outer sheath are polychloroprene rubber.

Typical applications

- Electric rope shovels, draglines and large excavators fed through a cable reel
- Bucket-wheel excavators, stackers and reclaimers in open-cast mines and bulk-material plants
- Mobile crushing and screening plants and relocatable conveyor drive stations
- Mobile transformer stations, skid-mounted switchgear and pump sets
- Ship-to-shore and harbour cranes fed from a reel at medium voltage
- Tunnelling machines and long-wall equipment with medium-voltage supply
- Steep ramps, shafts and long free-hanging lengths where the aramid braid carries the axial load
- Replacement of existing (N)TSCGEWöu cabling to DIN VDE 0250-813

8 sizes	3.6/6 kV	+90 °C	CR rubber
Cross-section 25 – 185 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CR rubber

Key features

- Individually screened cores with semi-conductive layers for 3.6/6 kV
- Split PE conductors in the outer interstices for a round, torsion-stable core
- Oil-resistant polychloroprene sheath; flame-retardant to IEC 60332-1-2
- Permanent tensile load 15 N/mm², dynamic load 30 N/mm² on the copper cross-section
- Reeling bending radius 12.5 × D, trailing 10 × D, fixed 6 × D
- Short-circuit temperature 250 °C; rated 90 °C at the conductor

© 2026 Anhui FeiChun Special Cable Co., Ltd.

- 8 sizes from 25 to 185 mm²; weight from 2,310 to 9,420 kg/km; copper from 990 to 6,270 kg/km

Core layout and conductor

Three power cores and three split protective conductors in the outer interstices of the stranded core, laid with a short lay length. The power cores are individually screened with semi-conductive layers and a copper braid. Two control cores of 1.5 mm² (blue, white) fill the free space between the power cores. The conductors are bare annealed copper. Bare copper has the lowest conductor resistance of the class 5 range and is the usual choice for dry and damp indoor use. Where the cable is exposed to salt, sulphur or permanent moisture, the tinned version of the same cable is preferable.

Standard background

DIN VDE 0250-813 defines the medium-voltage trailing cable (N)TSCGEWöu in the voltage classes 3.6/6 kV to 18/30 kV. The standard specifies the screened core design, the protective-conductor arrangement and the dimensional and test requirements; the R(N)TSCGEWöu version is the design for reeling duty.

A braid of aramid yarn between the inner and the outer sheath takes the axial load that would otherwise stretch the copper. It keeps the stranded cores from lengthening, prevents loops (“bird-caging”) when the cable is released from tension on a reel and raises the permissible working load above the copper-based rating. The load must be introduced through a clamp that holds the sheath and the braid, never through the conductors.


3.6/6 kV suits 6 kV systems. The insulation wall is 2.5 mm; the test voltage is 10 kV. In single-core designs the voltage class makes the cable markedly thicker than the 0.6/1 kV version.

02 Construction

FEICHUN · CROSS-SECTION A-A · 3.6/6 kV

(N)TSCGEWöu-C-HT

Sample size 3×70+3×35/3E+2×1.5 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Bare annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Semi-conductive layers and insulation	Inner and outer semi-conductive compound with EPR insulation (3GI3), extruded together
3	Core screen	Bare copper-wire braid, coverage ≥ 80 %
4	Split PE conductor	Class 5 copper, green-yellow insulation, laid in the outer interstices between the power cores
5	Control cores	Class 5 copper, blue and white insulation
6	Filler and binder tape	Rubber or compound filler with polyester binder tape
7	Inner sheath	Rubber compound, extruded over the stranded core
8	Tensile support braid	Aramid yarn braid between inner and outer sheath; carries the axial load
9	Outer sheath	Polychloroprene (CR) rubber, type 5GM5

The drawing shows size 3×70+3×35/3E+2×1.5. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Construction details

Conductor	Bare annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	EPR rubber, type 3GI3 (90 °C), maximum conductor temperature 90 °C
Core screen	Semi-conductive layers extruded with the insulation; bare copper-wire braid screen
Core identification	Power cores brown, black, grey; protective conductors green-yellow
Stranding	Power cores, split PE conductors and auxiliary elements stranded together with a short lay length
Inner sheath	Rubber compound; thickness about 1.0 mm at this size
Tensile support braid	Aramid yarn braid, 1.08 mm thick, between inner and outer sheath
Outer sheath	Polychloroprene (CR) rubber, type 5GM5; thickness about 1.3 mm at this size

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	3.6/6 kV AC
Test voltage	10 kV AC, 5 min
Maximum operating voltage, three-phase	7.2 kV
Maximum operating voltage, DC (core-earth / core-core)	5.4/10.8 kV
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, bare

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C (5 s maximum)
Ambient temperature, fixed installation	−40 °C to +80 °C
Ambient temperature, in motion	−25 °C to +80 °C
Minimum bending radius	Fixed: 6 × D; trailing: 10 × D; on a cable reel: 12.5 × D
Maximum tensile load	15 N/mm² on the copper cross-section plus the permissible load of the aramid support braid
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CR rubber)
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Damp and wet areas, spray water

04 Dimensions, Weights and Rated Data – 3.6/6 kV (8 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Outer Ø min mm	Outer Ø max mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
3×25+3×25/3E+2×1.5	FC-NTSC-0452-01	6.5	39.0	42.5	255	425	2,310	990	6,950	0.780	131	3.58
3×35+3×25/3E+2×1.5	FC-NTSC-0452-02	7.7	41.5	45.0	270	450	2,770	1,280	8,000	0.554	162	5.00
3×50+3×25/3E+2×1.5	FC-NTSC-0452-03	9.2	44.5	48.5	291	485	3,440	1,710	9,450	0.386	202	7.15
3×70+3×35/3E+2×1.5	FC-NTSC-0452-04	10.8	49.0	53.5	321	535	4,330	2,380	11,270	0.272	250	10.01
3×95+3×50/3E+2×1.5	FC-NTSC-0452-05	12.6	55.0	59.5	357	595	5,550	3,240	13,430	0.206	302	13.59
3×120+3×70/3E+2×1.5	FC-NTSC-0452-06	14.2	58.0	63.0	378	630	6,460	4,160	15,500	0.161	350	17.16
3×150+3×70/3E+2×1.5	FC-NTSC-0452-07	15.8	62.0	67.0	402	670	7,730	5,020	17,920	0.129	402	21.45
3×185+3×95/3E+2×1.5	FC-NTSC-0452-08	17.6	66.0	71.5	429	715	9,420	6,270	20,660	0.106	459	26.45

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below and the multi-core reduction factor already included in the table. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores plus the permissible load of the aramid braid.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.71

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Tensile Load, Reeling and Festoon Data

The values below support reel and festoon design: the permitted pull split into copper and braid parts, the free-hanging length (the length at which the cable's own weight reaches the rated pull, without a safety factor), the minimum reel core diameter and an indicative winding capacity for a reel with 2,500 mm flange diameter and 1,000 mm traverse width at 90 % fill. They are not a substitute for the reel manufacturer's calculation.

Type designation cores × mm²	Pull, copper N	Dynamic pull N	Pull, aramid braid N	Total permitted pull N	Free-hanging length m (vertical)	Min. reel core Ø mm	Winding capacity m (reel 2,500 × 1,000)
3×25+3×25/3E+2×1.5	1,120	8,080	5,830	6,950	306	1,062	1,815
3×35+3×25/3E+2×1.5	1,580	9,570	6,420	8,000	294	1,124	1,680
3×50+3×25/3E+2×1.5	2,250	11,700	7,200	9,450	280	1,212	1,355
3×70+3×35/3E+2×1.5	3,150	14,420	8,120	11,270	265	1,338	955
3×95+3×50/3E+2×1.5	4,280	17,700	9,150	13,430	246	1,488	710
3×120+3×70/3E+2×1.5	5,400	20,900	10,100	15,500	244	1,576	600
3×150+3×70/3E+2×1.5	6,750	24,670	11,170	17,920	236	1,676	495
3×185+3×95/3E+2×1.5	8,320	28,990	12,340	20,660	223	1,788	305

06 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 90 °C, cos φ = 0.8 and reactance 0.10 Ω/km (three-phase). The percentage refers to a system voltage of 6,000 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 90 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 6,000 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
3×25+3×25/3E+2×1.5	131	0.995	19.41	0.32	5.12	11.31	5.06	3.58	2.06
3×35+3×25/3E+2×1.5	162	0.706	17.54	0.29	5.56	15.83	7.08	5.00	2.89
3×50+3×25/3E+2×1.5	202	0.492	15.88	0.26	6.02	22.61	10.11	7.15	4.13
3×70+3×35/3E+2×1.5	250	0.347	14.61	0.24	6.50	31.65	14.16	10.01	5.78
3×95+3×50/3E+2×1.5	302	0.263	14.13	0.24	7.19	42.96	19.21	13.59	7.84
3×120+3×70/3E+2×1.5	350	0.205	13.59	0.23	7.54	54.26	24.27	17.16	9.91
3×150+3×70/3E+2×1.5	402	0.164	13.34	0.22	7.97	67.83	30.33	21.45	12.38
3×185+3×95/3E+2×1.5	459	0.135	13.37	0.22	8.54	83.66	37.41	26.45	15.27

07 Selection Guide and Sizing Aid

(N)TSCGEWöu-C-HT 3×+3E+2×1.5 covers 8 sizes. The smallest, 3×25+3×25/3E+2×1.5, has an outer diameter of up to 42.5 mm and weighs about 2,310 kg/km; the largest, 3×185+3×95/3E+2×1.5, has an outer diameter of up to 71.5 mm and weighs about 9,420 kg/km, 4.1 times as much. Across the range the rated current rises from 131 A to 459 A at 30 °C and the fixed bending radius from 255 mm to 429 mm.

Example 1. A circuit draws 136 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.91, grouping factor 0.80: required table current = 136 / (0.91 × 0.80) = 187 A. The smallest suitable size is 3×50+3×25/3E+2×1.5 with 202 A.

Example 2. A circuit draws 308 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.96: required table current = 308 / (0.96) = 322 A. The smallest suitable size is 3×120+3×70/3E+2×1.5 with 350 A.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

08 Engineering Profile by Size

Every size of (N)TSCGEWöu-C-HT 3×+3E+2×1.5 with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

3×25+3×25/3E+2×1.5. This size has with a conductor of Ø 6.5 mm under semi-conductive layers and EPR insulation (core Ø 16.1 mm) and 1.0 mm inner and 0.8 mm outer sheath; outer diameter 39.0–42.5 mm, weight about 2,310 kg/km of which copper 990 kg/km (43 %). Rated current 131 A at 30 °C; at that load the voltage drop is 19.41 V per 100 m (0.32 % of 6,000 V) and the loss 5.12 kW per 100 m. Bending radius 255 mm fixed, 425 mm moving; gland M63, lug bolt M8. Short-circuit rating 3.58 kA for 1 s; permitted pull 6,950 N, free-hanging length 306 m.

3×35+3×25/3E+2×1.5. This size has with a conductor of Ø 7.6 mm under semi-conductive layers and EPR insulation (core Ø 17.2 mm) and 1.0 mm inner and 0.8 mm outer sheath; outer diameter 41.5–45.0 mm, weight about 2,770 kg/km of which copper 1,280 kg/km (46 %). Rated current 162 A at 30 °C; at that load the voltage drop is 17.54 V per 100 m (0.29 % of 6,000 V) and the loss 5.56 kW per 100 m. Bending radius 270 mm fixed, 450 mm moving; gland M75, lug bolt M8. Short-circuit rating 5.00 kA for 1 s; permitted pull 8,000 N, free-hanging length 294 m.

3×50+3×25/3E+2×1.5. This size has with a conductor of Ø 9.1 mm under semi-conductive layers and EPR insulation (core Ø 18.7 mm) and 1.0 mm inner and 0.8 mm outer sheath; outer diameter 44.5–48.5 mm, weight about 3,440 kg/km of which copper 1,710 kg/km (50 %). Rated current 202 A at 30 °C; at that load the voltage drop is 15.88 V per 100 m (0.26 % of 6,000 V) and the loss 6.02 kW per 100 m. Bending radius 291 mm fixed, 485 mm moving; gland M75, lug bolt M10. Short-circuit rating 7.15 kA for 1 s; permitted pull 9,450 N, free-hanging length 280 m.

3×70+3×35/3E+2×1.5. This size has with a conductor of Ø 10.8 mm under semi-conductive layers and EPR insulation (core Ø 20.4 mm) and 1.0 mm inner and 1.3 mm outer sheath; outer diameter 49.0–53.5 mm, weight about 4,330 kg/km of which copper 2,380 kg/km (55 %). Rated current 250 A at 30 °C; at that load the voltage drop is 14.61 V per 100 m (0.24 % of 6,000 V) and the loss 6.50 kW per 100 m. Bending radius 321 mm fixed, 535 mm moving; gland M75, lug bolt M10. Short-circuit rating 10.01 kA for 1 s; permitted pull 11,270 N, free-hanging length 265 m.

3×95+3×50/3E+2×1.5. This size has with a conductor of Ø 12.6 mm under semi-conductive layers and EPR insulation (core Ø 22.2 mm) and 1.0 mm inner and 2.3 mm outer sheath; outer diameter 55.0–59.5 mm, weight about 5,550 kg/km of which copper 3,240 kg/km (58 %). Rated current 302 A at 30 °C; at that load the voltage drop is 14.13 V per 100 m (0.24 % of 6,000 V) and the loss 7.19 kW per 100 m. Bending radius 357 mm fixed, 595 mm moving; gland M85, lug bolt M12. Short-circuit rating 13.59 kA for 1 s; permitted pull 13,430 N, free-hanging length 246 m.

3×120+3×70/3E+2×1.5. This size has with a conductor of Ø 14.1 mm under semi-conductive layers and EPR insulation (core Ø 23.7 mm) and 1.0 mm inner and 2.2 mm outer sheath; outer diameter 58.0–63.0 mm, weight about 6,460 kg/km of which copper 4,160 kg/km (64 %). Rated current 350 A at 30 °C; at that load the voltage drop is 13.59 V per 100 m (0.23 % of 6,000 V) and the loss 7.54 kW per 100 m. Bending radius 378 mm fixed, 630 mm moving; gland M85, lug bolt M12. Short-circuit rating 17.16 kA for 1 s; permitted pull 15,500 N, free-hanging length 244 m.

3×150+3×70/3E+2×1.5. This size has with a conductor of Ø 15.8 mm under semi-conductive layers and EPR insulation (core Ø 25.4 mm) and 1.0 mm inner and 2.4 mm outer sheath; outer diameter 62.0–67.0 mm, weight about 7,730 kg/km of which copper 5,020 kg/km (65 %). Rated current 402 A at 30 °C; at that load the voltage drop is 13.34 V per 100 m (0.22 % of 6,000 V) and the loss 7.97 kW per 100 m. Bending radius 402 mm fixed, 670 mm moving; gland M90, lug bolt M12. Short-circuit rating 21.45 kA for 1 s; permitted pull 17,920 N, free-hanging length 236 m.

3×185+3×95/3E+2×1.5. This size has with a conductor of Ø 17.5 mm under semi-conductive layers and EPR insulation (core Ø 27.1 mm) and 1.0 mm inner and 2.6 mm outer sheath; outer diameter 66.0–71.5 mm, weight about 9,420 kg/km of which copper 6,270 kg/km (67 %). Rated current 459 A at 30 °C; at that load the voltage drop is 13.37 V per 100 m (0.22 % of 6,000 V) and the loss 8.54 kW per 100 m. Bending radius 429 mm fixed, 715 mm moving; gland M90, lug bolt M16. Short-circuit rating 26.45 kA for 1 s; permitted pull 20,660 N, free-hanging length 223 m.

Averaged over all sizes copper makes up 60 % of the cable weight; the share rises from 43 % at 3×25+3×25/3E+2×1.5 to 67 % at 3×185+3×95/3E+2×1.5, which is why the larger sizes are costed mostly on the copper market price.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

09 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 3.6/6 kV.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Laid-up core Ø mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
3×25+3×25/3E+2×1.5	6.45	16.05	semi-cond. + EPR	35.2	1.00	0.80	0.97	14
3×35+3×25/3E+2×1.5	7.63	17.23	semi-cond. + EPR	37.7	1.00	0.80	1.00	13
3×50+3×25/3E+2×1.5	9.12	18.72	semi-cond. + EPR	40.9	1.00	0.80	1.04	12
3×70+3×35/3E+2×1.5	10.79	20.39	semi-cond. + EPR	44.5	1.00	1.30	1.08	13
3×95+3×50/3E+2×1.5	12.57	22.17	semi-cond. + EPR	48.4	1.00	2.35	1.13	16
3×120+3×70/3E+2×1.5	14.13	23.73	semi-cond. + EPR	51.7	1.00	2.18	1.17	14
3×150+3×70/3E+2×1.5	15.80	25.40	semi-cond. + EPR	55.3	1.00	2.38	1.21	14
3×185+3×95/3E+2×1.5	17.55	27.15	semi-cond. + EPR	59.1	1.00	2.59	1.26	14

10 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
3×25+3×25/3E+2×1.5	42.5	M63	M8	14	130
3×35+3×25/3E+2×1.5	45.0	M75	M8	16	135
3×50+3×25/3E+2×1.5	48.5	M75	M10	19	145
3×70+3×35/3E+2×1.5	53.5	M75	M10	26	160
3×95+3×50/3E+2×1.5	59.5	M85	M12	31	180
3×120+3×70/3E+2×1.5	63.0	M85	M12	35	190
3×150+3×70/3E+2×1.5	67.0	M90	M12	41	200
3×185+3×95/3E+2×1.5	71.5	M90	M16	47	215

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

11 Comparison with Related Variants at Size 3×70+3×35/3E+2×1.5

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet (N)TSCGEWöu-C-HT 3×+3E+2×1.5 3.6/6 kV	–	53.5	4,330	11,270	250
(N)TSCGEWöu-P-HT 3×+3E+2×2.5 3.6/6 kV 3×70+3×35/3E+2×2.5	core configuration	53.5 (+0%)	4,350 (+0%)	11,270 (+0%)	250 (+0%)
(N)TSCGEWöu-F-HT 3×+3E+12FO 3.6/6 kV 3×70+3×35/3E+12FO	core configuration	54.5 (+2%)	4,370 (+1%)	11,540 (+2%)	250 (+0%)
(N)TSCGEWöu-C-HT 3×+3E+2×1.5 3.6/6 kV 3×70+3×35/3E+2×1.5	tinned vs bare copper	53.5 (+0%)	4,330 (+0%)	11,270 (+0%)	247 (-1%)
(N)TSCGEWöu-C 3×+3E+2×1.5 3.6/6 kV 3×70+3×35/3E+2×1.5	tensile braid	51.0 (-5%)	4,130 (-5%)	3,150 (-72%)	250 (+0%)
R(N)TSCGEWöu-C-HT 3×+3E+2×1.5 3.6/6 kV 3×70+3×35/3E+2×1.5	reeling design	53.5 (+0%)	4,330 (+0%)	11,270 (+0%)	250 (+0%)
(N)TSCGEWöu-C-HT 3×+3E+2×1.5 6/10 kV 3×70+3×35/3E+2×1.5	voltage class	57.5 (+7%)	4,670 (+8%)	12,310 (+9%)	250 (+0%)
(N)TSCGEWöu-HT 3×+3E 3.6/6 kV 3×70+3×35/3E	core configuration	53.5 (+0%)	4,300 (-1%)	11,270 (+0%)	250 (+0%)
(N)TSCGEWöu-C-HT 3×+3E+2×1.5 8.7/15 kV 3×70+3×35/3E+2×1.5	voltage class	62.5 (+17%)	5,100 (+18%)	13,670 (+21%)	257 (+3%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

12 Standards and Testing

Standard	Scope
DIN VDE 0250-813	Trailing cable (N)TSCGEWöu, 3.6/6 kV to 18/30 kV
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN VDE 0207-20 / -21	Rubber insulation and sheath compounds
DIN VDE 0298-3 / -4	Application and current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation
IEC 60502-2 (reference)	Partial-discharge and voltage testing practice for screened MV cores

Routine and type tests

- AC voltage test on every drum length (routine test): 10 kV, 5 min
- Partial-discharge test of the screened power cores
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors and protective earth
- Flame propagation test (IEC 60332-1-2) and mineral-oil resistance on type-test samples
- Tensile test of the finished cable and inspection of the aramid braid coverage (type test)

Test documentation: every delivery is accompanied by a test certificate from FeiChun’s own laboratory. Third-party witnessed tests can be arranged at the buyer’s cost.

The design follows DIN VDE 0250-813. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

13 Installation, Marking and Delivery

Installation guidance

- Terminate the core screens with MV accessories rated for the voltage class and ground the screens at both ends.
- Use a reel core diameter of at least 2 × the reeling bending radius; wind in orderly layers without cross-over.
- Avoid torsion above the limit agreed with FeiChun for the reel design; release twist before respooling.
- Connect all three split PE conductors at both ends.
- Lay drag cables on a prepared surface and protect them against vehicle crossings with cable ramps.
- Carry out a voltage test of the installed cable after termination, with the test voltage in the table of section 03.

Sheath marking

FEICHUN (N)TSCGEWöu-C-HT [cross-section] 3.6/6 kV [year] [serial no.] [metre mark]

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: (N)TSCGEWöu-C-HT 3×70+3×35/3E+2×1.5 3.6/6 kV – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (bare copper), length per piece, required standards and installation conditions.

14 Certification and Quality

All cable is subject to FeiChun’s quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

15 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- (N)TSCGEWöu-P-HT 3×+3E+2×2.5 3.6/6 kV – core configuration, CR rubber
- (N)TSCGEWöu-F-HT 3×+3E+12FO 3.6/6 kV – core configuration, CR rubber
- (N)TSCGEWöu-C-HT 3×+3E+2×1.5 3.6/6 kV – tinned vs bare copper, CR rubber, tinned
- (N)TSCGEWöu-C 3×+3E+2×1.5 3.6/6 kV – tensile braid, CR rubber
- R(N)TSCGEWöu-C-HT 3×+3E+2×1.5 3.6/6 kV – reeling design, CR rubber
- (N)TSCGEWöu-C-HT 3×+3E+2×1.5 6/10 kV – voltage class, CR rubber
- (N)TSCGEWöu-HT 3×+3E 3.6/6 kV – core configuration, CR rubber
- (N)TSCGEWöu-C-HT 3×+3E+2×1.5 8.7/15 kV – voltage class, CR rubber

Overview of all (N)TSCGEWöu datasheets: (N)TSCGEWöu Medium-Voltage Trailing Cables

Frequently asked questions

What does 3×50+3×25/3E mean?
Three power cores of 50 mm² and three protective (PE) conductors with a total cross-section of 25 mm² (the /3 divides it into three conductors), designated E.

What is the difference between (N)TSCGEWöu and R(N)TSCGEWöu?
The R version is designed for reeling duty with a lighter, more flexible core and a smaller permitted bending radius on the reel; the unprefixed version is the drag-cable design.

What sizes are available for (N)TSCGEWöu-C-HT 3×+3E+2×1.5?
8 sizes from 25 to 185 mm². The outer dimension of the largest size, 3×185+3×95/3E+2×1.5, is 71.5 mm and the weight is about 9,420 kg/km.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

What current can 3×95+3×50/3E+2×1.5 carry?
302 A in free air at 30 °C ambient, with the conductor at 90 °C. Other temperatures and grouping change the value; use the factors in section 04.

16 Trademark Notice and Intellectual Property

Cable type designations such as (N)TSCGEWöu-C-HT are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0452-EN
Revision 0 — first issue
Date 2 November 2026
Product (N)TSCGEWöu-C-HT 3.6/6 kV

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.