DIN VDE 0250-809 · FLAT RUBBER-SHEATHED CABLE · FESTOON DUTY | 0.6/1 kV | 6 sizes | CR rubber | BARE COPPER | REELING / FESTOON DUTY

NGFLGöu 7G 0.6/1 kV

Flat Rubber-Sheathed Flexible Cable 0.6/1 kV – 7 cores lie parallel in one plane, with the green-yellow core at the edge; a common flat sheath encloses them. Polychloroprene rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 6 sizes.

Document no. FC-TDS-VDE-2026-0631-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

NGFLGöu is the flat, polychloroprene-sheathed flexible cable of DIN VDE 0250-809 for festoon and trolley systems. 7 cores of fine-wire copper lie parallel in one plane and are enclosed by a common flat sheath of oil-resistant rubber. The flat shape lets the cable hang in even loops on a festoon rail, which is why it is used on overhead cranes, conveyor tail ends and monorail systems.

Design

The cores are EPR-insulated (type 3GI3) and are laid side by side with the green-yellow core at the edge; the remaining cores carry numbers. A rubber compound fills the space between the cores and is covered by a polychloroprene sheath that gives the cable a stable flat profile with rounded edges. Because the cores lie in one plane, the cable bends easily around the flat axis and is guided on festoon trolleys without twisting.

Typical applications

- Festoon systems on overhead and gantry cranes
- Conveyor tail-end and belt-tripper cars that travel on a rail
- Monorail and overhead rail transport in mines and factories
- Machine-tool and press loaders with horizontally travelling carriages
- Hoists and lifting platforms that need a flat, light feeder
- Stage and studio equipment with travelling lighting bars
- Warehouse shuttles and storage and retrieval machines
- Retrofit of flat cables to DIN VDE 0250-809 in existing festoon runs

6 sizes	0.6/1 kV	+90 °C	CR rubber
Cross-section 1.5 – 16 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CR rubber

Key features

- 7 cores in one plane, with a green-yellow core at the edge
- Flat profile 49.4 mm × 10.0 mm for the largest listed size: compact festoon loops
- EPR insulation rated 90 °C; short-circuit temperature 250 °C
- Oil-resistant, flame-retardant polychloroprene sheath
- Fine-wire class 5 conductors
- Bending radius 5 × H fixed, 8 × H in festoon operation (H = cable thickness)
- 6 sizes from 1.5 to 16 mm²; weight from 230 to 1,460 kg/km; copper from 101 to 1,080 kg/km

Core layout and conductor

7 cores lie parallel in one plane, with the green-yellow core at the edge; a common flat sheath encloses them. The conductors are bare annealed copper. Bare copper has the lowest conductor resistance of the class 5 range and is the usual choice for dry and damp indoor use. Where the cable is exposed to salt, sulphur or permanent moisture, the tinned version of the same cable is preferable.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Standard background

DIN VDE 0250-809 is the standard of the flat tough-rubber-sheathed flexible cable. It sets the number of cores, the conductor class, the insulation and sheath compounds and the flat dimensions that festoon rails and cable trolleys are designed around.

The standard sheath compound is flexible down to 25 °C in motion and 40 °C in fixed installation. For regular use below this limit select the low-temperature grade of the same cable.


0.6/1 kV (rated phase-to-earth / phase-to-phase voltage) covers 400 V and 690 V three-phase systems; the test voltage is 3 kV.

02 Construction

FEICHUN · CROSS-SECTION A-A · 0.6/1 kV

NGFLGöu

Sample size 7G4 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Bare annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Insulation	EPR rubber, type 3GI3 (90 °C)
3	Protective (PE) core	Green-yellow insulation, same cross-section as the power cores
4	Outer sheath	Polychloroprene (CR) rubber, type 5GM5

The drawing shows size 7G4. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

Construction details

Conductor	Bare annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	EPR rubber, type 3GI3 (90 °C), maximum conductor temperature 90 °C
Core identification	Green-yellow core at the edge; remaining cores black with white numbers
Stranding	Cores laid parallel in one plane
Outer sheath	Polychloroprene (CR) rubber, type 5GM5; thickness about 1.6 mm at this size

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	0.6/1 kV AC
Test voltage	3 kV AC, 5 min
Maximum operating voltage, three-phase	1.2 kV
Maximum operating voltage, DC (core-earth / core-core)	0.9/1.8 kV
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, bare

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C (5 s maximum)
Ambient temperature, fixed installation	−40 °C to +80 °C
Ambient temperature, in motion	−25 °C to +80 °C
Minimum bending radius	Fixed: 5 × H; festoon operation: 8 × H (H = cable thickness)
Maximum tensile load	15 N/mm² continuous on the total copper cross-section
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CR rubber)
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Damp and wet areas, spray water

04 Dimensions, Weights and Rated Data – 0.6/1 kV (6 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Width mm	Height mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
7G1.5	FC-NGFL-0631-01	1.7	23.7	5.4	27	43	230	101	158	13.3	14	0.214
7G2.5	FC-NGFL-0631-02	2.2	27.1	5.9	29	47	321	168	262	7.98	20	0.357
7G4	FC-NGFL-0631-03	2.7	31.9	7.3	37	58	490	269	420	4.95	27	0.572
7G6	FC-NGFL-0631-04	3.3	36.2	8.0	40	64	660	400	630	3.30	35	0.858
7G10	FC-NGFL-0631-05	4.1	41.7	8.8	44	71	980	670	1,050	1.91	48	1.43
7G16	FC-NGFL-0631-06	5.2	49.4	10.0	50	80	1,460	1,080	1,680	1.21	64	2.29

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below and the multi-core reduction factor already included in the table. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores. Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.71

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Tensile Load, Reeling and Festoon Data

The values below support reel and festoon design: the permitted pull split into copper and braid parts, the free-hanging length (the length at which the cable's own weight reaches the rated pull, without a safety factor), the minimum reel core diameter and an indicative winding capacity for a reel with 2,500 mm flange diameter and 1,000 mm traverse width at 90 % fill. They are not a substitute for the reel manufacturer's calculation.

Type designation cores × mm²	Pull, copper N	Total permitted pull N	Free-hanging length m (vertical)	Min. festoon loop Ø mm
7G1.5	158	158	70	86
7G2.5	262	262	83	94
7G4	420	420	87	116
7G6	630	630	97	128
7G10	1,050	1,050	109	142
7G16	1,680	1,680	117	160

© 2026 Anhui FeiChun Special Cable Co., Ltd.

06 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 90 °C, cos φ = 0.8 and reactance 0.08 Ω/km (three-phase). The percentage refers to a system voltage of 400 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 90 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 400 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
7G1.5	14	17.0	33.01	8.25	1.00	0.678	0.303	0.214	0.124
7G2.5	20	10.2	28.36	7.09	1.22	1.13	0.506	0.357	0.206
7G4	27	6.31	23.84	5.96	1.38	1.81	0.809	0.572	0.330
7G6	35	4.21	20.70	5.17	1.55	2.71	1.21	0.858	0.495
7G10	48	2.44	16.60	4.15	1.68	4.52	2.02	1.43	0.826
7G16	64	1.54	14.21	3.55	1.90	7.24	3.24	2.29	1.32

07 Selection Guide and Sizing Aid

NGFLGöu 7G covers 6 sizes. The smallest, 7G1.5, has 23.7 × 5.4 mm and weighs about 230 kg/km; the largest, 7G16, has 49.4 × 10.0 mm and weighs about 1,460 kg/km, 6.3 times as much. Across the range the rated current rises from 14 A to 64 A at 30 °C and the fixed bending radius from 27 mm to 50 mm.

Example 1. A circuit draws 18 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.91, grouping factor 0.80: required table current = 18 / (0.91 × 0.80) = 25 A. The smallest suitable size is 7G4 with 27 A.

Example 2. A circuit draws 42 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.96: required table current = 42 / (0.96) = 44 A. The smallest suitable size is 7G10 with 48 A.

08 Engineering Profile by Size

Every size of NGFLGöu 7G with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

7G1.5. This size has with a conductor of Ø 1.7 mm under 0.70 mm of insulation (core Ø 3.1 mm) and an outer sheath of 1.2 mm; 23.7 × 5.4 mm (W × H), weight about 230 kg/km of which copper 101 kg/km (44 %). Rated current 14 A at 30 °C; at that load the voltage drop is 33.01 V per 100 m (8.25 % of 400 V) and the loss 1.00 kW per 100 m. Bending radius 27 mm fixed, 43 mm moving; gland flat, lug bolt M5. Short-circuit rating 0.214 kA for 1 s; permitted pull 158 N, free-hanging length 70 m.

7G2.5. This size has with a conductor of Ø 2.1 mm under 0.70 mm of insulation (core Ø 3.5 mm) and an outer sheath of 1.2 mm; 27.1 × 5.9 mm (W × H), weight about 321 kg/km of which copper 168 kg/km (52 %). Rated current 20 A at 30 °C; at that load the voltage drop is 28.36 V per 100 m (7.09 % of 400 V) and the loss 1.22 kW per 100 m. Bending radius 29 mm fixed, 47 mm moving; gland flat, lug bolt M5. Short-circuit rating 0.357 kA for 1 s; permitted pull 262 N, free-hanging length 83 m.

7G4. This size has with a conductor of Ø 2.7 mm under 0.70 mm of insulation (core Ø 4.1 mm) and an outer sheath of 1.6 mm; 31.9 × 7.3 mm (W × H), weight about 490 kg/km of which copper 269 kg/km (55 %). Rated current 27 A at 30 °C; at that load the voltage drop is 23.84 V per 100 m (5.96 % of 400 V) and the loss 1.38 kW per 100 m. Bending radius 37 mm fixed, 58 mm moving; gland flat, lug bolt M5. Short-circuit rating 0.572 kA for 1 s; permitted pull 420 N, free-hanging length 87 m.

7G6. This size has with a conductor of Ø 3.3 mm under 0.70 mm of insulation (core Ø 4.7 mm) and an outer sheath of 1.6 mm; 36.2 × 8.0 mm (W × H), weight about 660 kg/km of which copper 400 kg/km (61 %). Rated current 35 A at 30 °C; at that load the voltage drop is 20.70 V per 100 m (5.17 % of 400 V) and the loss 1.55 kW per 100 m. Bending radius 40 mm fixed, 64 mm moving; gland flat, lug bolt M5. Short-circuit rating 0.858 kA for 1 s; permitted pull 630 N, free-hanging length 97 m.

7G10. This size has with a conductor of Ø 4.1 mm under 0.70 mm of insulation (core Ø 5.5 mm) and an outer sheath of 1.7 mm; 41.7 × 8.8 mm (W × H), weight about 980 kg/km of which copper 670 kg/km (68 %). Rated current 48 A at 30 °C; at that load the voltage drop is 16.60 V per 100 m (4.15 % of 400 V) and the loss 1.68 kW per 100 m. Bending radius 44 mm fixed, 71 mm moving; gland flat, lug bolt M6. Short-circuit rating 1.43 kA for 1 s; permitted pull 1,050 N, free-hanging length 109 m.

7G16. This size has with a conductor of Ø 5.2 mm under 0.70 mm of insulation (core Ø 6.6 mm) and an outer sheath of 1.7 mm; 49.4 × 10.0 mm (W × H), weight about 1,460 kg/km of which copper 1,080 kg/km (74 %). Rated current 64 A at 30 °C; at that load the voltage drop is 14.21 V per 100 m (3.55 % of 400 V) and the loss 1.90 kW per 100 m. Bending radius 50 mm fixed, 80 mm moving; gland flat, lug bolt M6. Short-circuit rating 2.29 kA for 1 s; permitted pull

© 2026 Anhui FeiChun Special Cable Co., Ltd.

1,680 N, free-hanging length 117 m.

Averaged over all sizes copper makes up 65 % of the cable weight; the share rises from 44 % at 7G1.5 to 74 % at 7G16, which is why the larger sizes are costed mostly on the copper market price.

09 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 0.6/1 kV.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Core row width mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
7G1.5	1.65	3.05	0.70	21.4	–	1.15	–	43
7G2.5	2.13	3.53	0.70	24.7	–	1.18	–	40
7G4	2.70	4.10	0.70	28.7	–	1.60	–	44
7G6	3.30	4.70	0.70	32.9	–	1.64	–	41
7G10	4.08	5.48	0.70	38.4	–	1.67	–	38
7G16	5.16	6.56	0.70	45.9	–	1.73	–	35

10 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
7G1.5	23.7 × 5.4	flat gland	M5	10	15
7G2.5	27.1 × 5.9	flat gland	M5	10	15
7G4	31.9 × 7.3	flat gland	M5	10	20
7G6	36.2 × 8.0	flat gland	M5	11	20
7G10	41.7 × 8.8	flat gland	M6	11	20
7G16	49.4 × 10.0	flat gland	M6	12	25

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

11 Comparison with Related Variants at Size 7G4

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet NGFLGöu 7G 0.6/1 kV	–	7.3	490	420	27
NGFLGöu 6G 0.6/1 kV 6G4	core configuration	7.3 (+0%)	420 (-14%)	360 (-14%)	29 (+7%)
NGFLGöu 8G 0.6/1 kV 8G4	core configuration	7.3 (+0%)	560 (+14%)	480 (+14%)	25 (-7%)
NGFLGöu 7G 0.6/1 kV 7G4	tinned vs bare copper	7.3 (+0%)	490 (+0%)	420 (+0%)	27 (+0%)
NGFLGöu 7G 0.6/1 kV 7G4	low-temperature sheath	7.3 (+0%)	490 (+0%)	420 (+0%)	27 (+0%)
NGFLGöu 7G 0.66/1.14 kV 7G4	voltage class	7.5 (+3%)	510 (+4%)	420 (+0%)	27 (+0%)
NGFLGöu 5G 0.6/1 kV 5G4	core configuration	7.3 (+0%)	354 (-28%)	300 (-29%)	33 (+22%)
NGFLGöu 10G 0.6/1 kV 10G4	core configuration	7.3 (+0%)	700 (+43%)	600 (+43%)	22 (-19%)
NGFLGöu 4G 0.6/1 kV 4G4	core configuration	7.3 (+0%)	285 (-42%)	240 (-43%)	38 (+41%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

12 Standards and Testing

Standard	Scope
DIN VDE 0250-809	Flat tough-rubber-sheathed flexible cable
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN VDE 0207-20 / -21	Rubber insulation and sheath compounds
DIN VDE 0298-3 / -4	Application and current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation

Routine and type tests

- AC voltage test on every drum length (routine test): 3 kV, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors and protective earth
- Flame propagation test (IEC 60332-1-2) and mineral-oil resistance on type-test samples
- Bending and torsion tests for reeling duty (type test)

Test documentation: every delivery is accompanied by a test certificate from FeiChun's own laboratory. Third-party witnessed tests can be arranged at the buyer's cost.

The design follows DIN VDE 0250-809. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

13 Installation, Marking and Delivery

Installation guidance

- Hang the cable on its flat side only; never let it twist around its longitudinal axis in the festoon loop.
- Keep the loop diameter at or above twice the bending radius of the table.
- Use trolleys with a rounded cable clamp that spreads the clamping force across the flat width.
- Provide a free loop at both ends so that travel does not pull on the terminations.
- Separate the cable from sharp rail edges with protective profiles.
- Leave the green-yellow core slightly longer than the others at the terminal.

Sheath marking

FEICHUN NGFLGöu [cross-section] 0.6/1 kV [year] [serial no.] [metre mark]

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: NGFLGöu 7G4 0.6/1 kV – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (bare copper), length per piece, required standards and installation conditions.

14 Certification and Quality

All cable is subject to FeiChun's quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

15 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- NGFLGöu 6G 0.6/1 kV – core configuration, CR rubber
- NGFLGöu 8G 0.6/1 kV – core configuration, CR rubber
- NGFLGöu 7G 0.6/1 kV – tinned vs bare copper, CR rubber, tinned

© 2026 Anhui FeiChun Special Cable Co., Ltd.

- NGFLGöu 7G 0.6/1 kV – low-temperature sheath, CR rubber, low-temp
- NGFLGöu 7G 0.66/1.14 kV – voltage class, CR rubber
- NGFLGöu 5G 0.6/1 kV – core configuration, CR rubber
- NGFLGöu 10G 0.6/1 kV – core configuration, CR rubber
- NGFLGöu 4G 0.6/1 kV – core configuration, CR rubber

Overview of all NGFLGöu datasheets: NGFLGöu Flat Rubber-Sheathed Cables

Frequently asked questions

Why use a flat cable?
A flat cable hangs in uniform loops and takes less festoon height than a round cable of the same core count.

How many cores does NGFLGöu 7G have?
7 cores, including one green-yellow protective core.

What sizes are available for NGFLGöu 7G?
6 sizes from 1.5 to 16 mm². The outer dimension of the largest size, 7G16, is 10.0 mm and the weight is about 1,460 kg/km.

What current can 7G6 carry?
35 A in free air at 30 °C ambient, with the conductor at 90 °C. Other temperatures and grouping change the value; use the factors in section 04.

16 Trademark Notice and Intellectual Property

Cable type designations such as NGFLGöu are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0631-EN
Revision 0 — first issue
Date 2 November 2026
Product NGFLGöu 0.6/1 kV

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.