DIN VDE 0250-814 · HEAVY RUBBER TRAILING CABLE · CRANES AND REELS | 0.6/1 kV | 13 sizes | CR rubber, low-temp | BARE COPPER | LOW-TEMPERATURE GRADE | TENSILE SUPPORT BRAID | REELING / FESTOON DUTY

NSHTöu 4× 0.6/1 kV

Heavy Rubber Trailing Cable with Tensile Support 0.6/1 kV – 4 cores of equal cross-section in concentric layers with a short lay length. Low-temperature polychloroprene rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 13 sizes.

Document no. FC-TDS-VDE-2026-0331-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

NSHTöu is the heavy rubber trailing cable for cranes, reels and festoon systems that move under tension. The design follows DIN VDE 0250-814: EPR/HEPR-insulated cores of fine-wire copper are stranded with a short lay length, a rubber inner sheath carries a tensile support element and an oil-resistant polychloroprene outer sheath protects the cable. Compared with a plain NSHTöu cable the tensile support allows a permanent load of 15 N/mm² and a dynamic load of 30 N/mm² on the copper cross-section.

Design

The cores are insulated with rubber of type 3GI3 (HEPR) for 90 °C at the conductor. Cores and protective conductors are stranded in short-lay layers; in the three-core designs with split PE the protective conductors lie in the outer interstices, so that the power cores form a compact, balanced triangle. A rubber inner sheath is extruded over the stranded core; an aramid tensile support braid bedded between the sheaths takes the axial load; the outer sheath is polychloroprene 5GM5. The construction keeps the copper free of tension, which is what extends cable life on reels and cranes.

Typical applications

- Crane, hoist and bridge-crane trailing cables with a cable chain or festoon trolley
- Cable reels of bucket-wheel excavators, stackers, reclaimers and portal cranes
- Mobile harbour and container equipment with repeated winding and unwinding
- Mining machinery, drilling rigs and shuttle systems that carry the cable under tension
- Mobile crushing and screening plants fed from a reel or a drag-cable arrangement
- Industrial hoisting systems with long free-hanging lengths
- Tunnelling machines and transfer cars with tensile and torsional loading
- Cold-climate duty: sites, cold stores and open-cast operations where the cable is moved at temperatures down to 40 °C

13 sizes	0.6/1 kV	+90 °C	CR rubber, low-temp
Cross-section 1.5 – 150 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CR rubber, low-temp

Key features

- Aramid tensile support braid: permanent load 15 N/mm², dynamic load 30 N/mm² on the copper cross-section
- HEPR insulation, 90 °C at the conductor, short-circuit temperature 250 °C
- Reeling-duty bending radii of 6 × D to 10 × D depending on diameter
- Oil-resistant polychloroprene sheath, flame-retardant to IEC 60332-1-2
- Split PE conductors in the outer interstices (3×+3E designs) for a round, compact core
- Fine-wire class 5 conductors, bare or tinned

© 2026 Anhui FeiChun Special Cable Co., Ltd.

- 13 sizes from 1.5 to 150 mm²; weight from 271 to 8,030 kg/km; copper from 58 to 5,760 kg/km

Core layout and conductor

4 cores of equal cross-section in concentric layers with a short lay length. Core colours: blue, brown, black, grey (DIN VDE 0293-308); no protective core is included. The four-core layout carries three phases and PE (4G) or three phases and neutral (4×). The conductors are bare annealed copper. Bare copper has the lowest conductor resistance of the class 5 range and is the usual choice for dry and damp indoor use. Where the cable is exposed to salt, sulphur or permanent moisture, the tinned version of the same cable is preferable.

Standard background

DIN VDE 0250-814 describes the NSHTöu rubber trailing cable. The standard adds a tensile-bearing element to the heavy rubber-sheathed design so that the cable can be used as a trailing, reeling or festoon cable under tension. For sizes from 25 mm² the split-PE 3×+3E designs are the usual choice for crane and reel feeds.

The low-temperature grade of the sheath compound remains flexible down to 40 °C in motion and 50 °C in fixed installation, so the cable can be reeled and trailed on cold sites, in cold stores and in northern open-cast operations. The mechanical and electrical ratings are those of the standard grade; only the cold-flexing limit is extended.

A braid of aramid yarn between the inner and the outer sheath takes the axial load that would otherwise stretch the copper. It keeps the stranded cores from lengthening, prevents loops (“bird-caging”) when the cable is released from tension on a reel and raises the permissible working load above the copper-based rating. The load must be introduced through a clamp that holds the sheath and the braid, never through the conductors.


0.6/1 kV (rated phase-to-earth / phase-to-phase voltage) covers 400 V and 690 V three-phase systems; the test voltage is 3 kV.

02 Construction

FEICHUN · CROSS-SECTION A-A · 0.6/1 kV

NSHTöu

Sample size 4×25 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Bare annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Insulation	HEPR rubber, type 3GI3 (90 °C)
3	Filler and binder tape	Rubber or compound filler with polyester binder tape
4	Inner sheath	Rubber compound, extruded over the stranded core
5	Tensile support braid	Aramid yarn braid between inner and outer sheath; carries the axial load
6	Outer sheath	Polychloroprene (CR) rubber, low-temperature grade

The drawing shows size 4×25. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Construction details

Conductor	Bare annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	HEPR rubber, type 3GI3 (90 °C), maximum conductor temperature 90 °C
Core identification	Blue, brown, black, grey to DIN VDE 0293-308
Stranding	Cores in concentric layers with a short lay length
Inner sheath	Rubber compound; thickness about 2.0 mm at this size
Tensile support braid	Aramid yarn braid, 0.80 mm thick, between inner and outer sheath
Outer sheath	Polychloroprene (CR) rubber, low-temperature grade; thickness about 6.2 mm at this size

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	0.6/1 kV AC
Test voltage	3 kV AC, 5 min
Maximum operating voltage, three-phase	1.2 kV
Maximum operating voltage, DC (core-earth / core-core)	0.9/1.8 kV
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, bare

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C (5 s maximum)
Ambient temperature, fixed installation	−50 °C to +80 °C
Ambient temperature, in motion	−40 °C to +80 °C
Minimum bending radius	Fixed: 3 × D (D ≤ 12 mm), 4 × D (D > 12 mm); moving: 4 × D (≤ 12 mm), 5 × D (≤ 20 mm), 6 × D (> 20 mm); reeling: 6 to 10 × D
Maximum tensile load	Permanent 15 N/mm², dynamic 30 N/mm² on the total copper cross-section of the power cores (including the aramid support braid)
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CR rubber, low-temp)
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Damp and wet areas, spray water

© 2026 Anhui FeiChun Special Cable Co., Ltd.

04 Dimensions, Weights and Rated Data – 0.6/1 kV (13 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Outer Ø min mm	Outer Ø max mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
4×1.5	FC-NSHT-0331-01	1.7	15.2	17.3	69	86	271	58	1,190	13.3	19	0.214
4×2.5	FC-NSHT-0331-02	2.2	17.5	19.8	79	99	388	96	1,420	7.98	26	0.357
4×4	FC-NSHT-0331-03	2.7	20.0	22.8	91	137	520	154	1,700	4.95	35	0.572
4×6	FC-NSHT-0331-04	3.3	22.0	25.0	100	150	650	230	2,040	3.30	46	0.858
4×10	FC-NSHT-0331-05	4.1	25.5	29.0	116	174	1,010	384	2,580	1.91	63	1.43
4×16	FC-NSHT-0331-06	5.2	28.5	32.5	130	195	1,520	610	3,370	1.21	84	2.29
4×25	FC-NSHT-0331-07	6.5	36.0	41.0	164	246	2,120	960	4,660	0.780	111	3.58
4×35	FC-NSHT-0331-08	7.7	39.0	44.5	178	267	2,850	1,340	5,820	0.554	137	5.00
4×50	FC-NSHT-0331-09	9.2	45.0	51.0	204	306	3,890	1,920	7,580	0.386	172	7.15
4×70	FC-NSHT-0331-10	10.8	51.0	58.0	232	348	4,260	2,690	9,710	0.272	212	10.01
4×95	FC-NSHT-0331-11	12.6	58.0	66.0	264	396	5,320	3,650	12,400	0.206	257	13.59
4×120	FC-NSHT-0331-12	14.2	64.0	72.5	290	435	6,650	4,610	14,900	0.161	297	17.16
4×150	FC-NSHT-0331-13	15.8	70.0	79.5	318	477	8,030	5,760	18,270	0.129	342	21.45

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below and the multi-core reduction factor already included in the table. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores plus the permissible load of the aramid braid. Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.71

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Tensile Load, Reeling and Festoon Data

The values below support reel and festoon design: the permitted pull split into copper and braid parts, the free-hanging length (the length at which the cable's own weight reaches the rated pull, without a safety factor), the minimum reel core diameter and an indicative winding capacity for a reel with 2,500 mm flange diameter and 1,000 mm traverse width at 90 % fill. They are not a substitute for the reel manufacturer's calculation.

Type designation cores × mm²	Pull, copper N	Dynamic pull N	Pull, aramid braid N	Total permitted pull N	Free-hanging length m (vertical)	Min. reel core Ø mm	Winding capacity m (reel 2,500 × 1,000)
4×1.5	90	1,280	1,100	1,190	447	276	14,265
4×2.5	150	1,570	1,270	1,420	373	316	10,925
4×4	240	1,940	1,460	1,700	333	456	7,805
4×6	360	2,400	1,680	2,040	319	500	6,785
4×10	600	3,180	1,980	2,580	260	580	4,875
4×16	960	4,330	2,410	3,370	226	650	3,705
4×25	1,500	6,160	3,160	4,660	224	820	2,225
4×35	2,100	7,920	3,720	5,820	208	890	1,895
4×50	3,000	10,580	4,580	7,580	198	1,020	1,305
4×70	4,200	13,910	5,510	9,710	232	1,160	950
4×95	5,700	18,100	6,700	12,400	237	1,320	625
4×120	7,200	22,100	7,700	14,900	228	1,450	505
4×150	9,000	27,270	9,270	18,270	231	1,590	335

© 2026 Anhui FeiChun Special Cable Co., Ltd.

06 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 90 °C, cos φ = 0.8 and reactance 0.08 Ω/km (three-phase). The percentage refers to a system voltage of 400 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 90 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 400 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
4×1.5	19	17.0	44.81	11.20	1.84	0.678	0.303	0.214	0.124
4×2.5	26	10.2	36.87	9.22	2.06	1.13	0.506	0.357	0.206
4×4	35	6.31	30.90	7.73	2.32	1.81	0.809	0.572	0.330
4×6	46	4.21	27.20	6.80	2.67	2.71	1.21	0.858	0.495
4×10	63	2.44	21.78	5.45	2.90	4.52	2.02	1.43	0.826
4×16	84	1.54	18.66	4.66	3.27	7.24	3.24	2.29	1.32
4×25	111	0.995	16.22	4.06	3.68	11.31	5.06	3.58	2.06
4×35	137	0.706	14.55	3.64	3.98	15.83	7.08	5.00	2.89
4×50	172	0.492	13.16	3.29	4.37	22.61	10.11	7.15	4.13
4×70	212	0.347	11.95	2.99	4.68	31.65	14.16	10.01	5.78
4×95	257	0.263	11.49	2.87	5.20	42.96	19.21	13.59	7.84
4×120	297	0.205	10.92	2.73	5.43	54.26	24.27	17.16	9.91
4×150	342	0.164	10.64	2.66	5.77	67.83	30.33	21.45	12.38

07 Selection Guide and Sizing Aid

NSHTöu 4× covers 13 sizes. The smallest, 4×1.5, has an outer diameter of up to 17.3 mm and weighs about 271 kg/km; the largest, 4×150, has an outer diameter of up to 79.5 mm and weighs about 8,030 kg/km, 29.6 times as much. Across the range the rated current rises from 19 A to 342 A at 30 °C and the fixed bending radius from 69 mm to 318 mm.

Example 1. A circuit draws 42 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.91, grouping factor 0.80: required table current = 42 / (0.91 × 0.80) = 58 A. The smallest suitable size is 4×10 with 63 A.

Example 2. A circuit draws 152 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.96: required table current = 152 / (0.96) = 159 A. The smallest suitable size is 4×50 with 172 A.

08 Engineering Profile by Size

Every size of NSHTöu 4× with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

4×1.5. This size has with a conductor of Ø 1.7 mm under 0.70 mm of insulation (core Ø 3.1 mm) and 1.1 mm inner and 2.4 mm outer sheath; outer diameter 15.2–17.3 mm, weight about 271 kg/km of which copper 58 kg/km (21 %). Rated current 19 A at 30 °C; at that load the voltage drop is 44.81 V per 100 m (11.20 % of 400 V) and the loss 1.84 kW per 100 m. Bending radius 69 mm fixed, 86 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.214 kA for 1 s; permitted pull 1,190 N, free-hanging length 447 m.

4×2.5. This size has with a conductor of Ø 2.1 mm under 0.70 mm of insulation (core Ø 3.5 mm) and 1.2 mm inner and 2.9 mm outer sheath; outer diameter 17.5–19.8 mm, weight about 388 kg/km of which copper 96 kg/km (25 %). Rated current 26 A at 30 °C; at that load the voltage drop is 36.87 V per 100 m (9.22 % of 400 V) and the loss 2.06 kW per 100 m. Bending radius 79 mm fixed, 99 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.357 kA for 1 s; permitted pull 1,420 N, free-hanging length 373 m.

4×4. This size has with a conductor of Ø 2.7 mm under 0.70 mm of insulation (core Ø 4.1 mm) and 1.3 mm inner and 3.5 mm outer sheath; outer diameter 20.0–22.8 mm, weight about 520 kg/km of which copper 154 kg/km (30 %). Rated current 35 A at 30 °C; at that load the voltage drop is 30.90 V per 100 m (7.73 % of 400 V) and the loss 2.32 kW per 100 m. Bending radius 91 mm fixed, 137 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.572 kA for 1 s; permitted pull 1,700 N, free-hanging length 333 m.

4×6. This size has with a conductor of Ø 3.3 mm under 0.70 mm of insulation (core Ø 4.7 mm) and 1.4 mm inner and 3.7 mm outer sheath; outer diameter 22.0–25.0 mm, weight about 650 kg/km of which copper 230 kg/km (35 %). Rated current 46 A at 30 °C; at that load the voltage drop is 27.20 V per 100 m (6.80 % of 400 V) and the loss 2.67 kW per 100 m. Bending radius 100 mm fixed, 150 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.858 kA for 1 s; permitted pull 2,040 N, free-hanging length 319 m.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

4×10. This size has with a conductor of Ø 4.1 mm under 0.70 mm of insulation (core Ø 5.5 mm) and 1.5 mm inner and 4.5 mm outer sheath; outer diameter 25.5–29.0 mm, weight about 1,010 kg/km of which copper 384 kg/km (38 %). Rated current 63 A at 30 °C; at that load the voltage drop is 21.78 V per 100 m (5.45 % of 400 V) and the loss 2.90 kW per 100 m. Bending radius 116 mm fixed, 174 mm moving; gland M40, lug bolt M6. Short-circuit rating 1.43 kA for 1 s; permitted pull 2,580 N, free-hanging length 260 m.

4×16. This size has with a conductor of Ø 5.2 mm under 0.70 mm of insulation (core Ø 6.6 mm) and 1.7 mm inner and 4.7 mm outer sheath; outer diameter 28.5–32.5 mm, weight about 1,520 kg/km of which copper 610 kg/km (40 %). Rated current 84 A at 30 °C; at that load the voltage drop is 18.66 V per 100 m (4.66 % of 400 V) and the loss 3.27 kW per 100 m. Bending radius 130 mm fixed, 195 mm moving; gland M50, lug bolt M6. Short-circuit rating 2.29 kA for 1 s; permitted pull 3,370 N, free-hanging length 226 m.

4×25. This size has with a conductor of Ø 6.5 mm under 0.90 mm of insulation (core Ø 8.3 mm) and 2.0 mm inner and 6.2 mm outer sheath; outer diameter 36.0–41.0 mm, weight about 2,120 kg/km of which copper 960 kg/km (45 %). Rated current 111 A at 30 °C; at that load the voltage drop is 16.22 V per 100 m (4.06 % of 400 V) and the loss 3.68 kW per 100 m. Bending radius 164 mm fixed, 246 mm moving; gland M63, lug bolt M8. Short-circuit rating 3.58 kA for 1 s; permitted pull 4,660 N, free-hanging length 224 m.

4×35. This size has with a conductor of Ø 7.6 mm under 0.90 mm of insulation (core Ø 9.4 mm) and 2.2 mm inner and 6.2 mm outer sheath; outer diameter 39.0–44.5 mm, weight about 2,850 kg/km of which copper 1,340 kg/km (47 %). Rated current 137 A at 30 °C; at that load the voltage drop is 14.55 V per 100 m (3.64 % of 400 V) and the loss 3.98 kW per 100 m. Bending radius 178 mm fixed, 267 mm moving; gland M75, lug bolt M8. Short-circuit rating 5.00 kA for 1 s; permitted pull 5,820 N, free-hanging length 208 m.

4×50. This size has with a conductor of Ø 9.1 mm under 1.00 mm of insulation (core Ø 11.1 mm) and 2.4 mm inner and 7.0 mm outer sheath; outer diameter 45.0–51.0 mm, weight about 3,890 kg/km of which copper 1,920 kg/km (49 %). Rated current 172 A at 30 °C; at that load the voltage drop is 13.16 V per 100 m (3.29 % of 400 V) and the loss 4.37 kW per 100 m. Bending radius 204 mm fixed, 306 mm moving; gland M75, lug bolt M10. Short-circuit rating 7.15 kA for 1 s; permitted pull 7,580 N, free-hanging length 198 m.

4×70. This size has with a conductor of Ø 10.8 mm under 1.00 mm of insulation (core Ø 12.8 mm) and 2.7 mm inner and 7.8 mm outer sheath; outer diameter 51.0–58.0 mm, weight about 4,260 kg/km of which copper 2,690 kg/km (63 %). Rated current 212 A at 30 °C; at that load the voltage drop is 11.95 V per 100 m (2.99 % of 400 V) and the loss 4.68 kW per 100 m. Bending radius 232 mm fixed, 348 mm moving; gland M85, lug bolt M10. Short-circuit rating 10.01 kA for 1 s; permitted pull 9,710 N, free-hanging length 232 m.

4×95. This size has with a conductor of Ø 12.6 mm under 1.10 mm of insulation (core Ø 14.8 mm) and 3.0 mm inner and 8.8 mm outer sheath; outer diameter 58.0–66.0 mm, weight about 5,320 kg/km of which copper 3,650 kg/km (69 %). Rated current 257 A at 30 °C; at that load the voltage drop is 11.49 V per 100 m (2.87 % of 400 V) and the loss 5.20 kW per 100 m. Bending radius 264 mm fixed, 396 mm moving; gland M90, lug bolt M12. Short-circuit rating 13.59 kA for 1 s; permitted pull 12,400 N, free-hanging length 237 m.

4×120. This size has with a conductor of Ø 14.1 mm under 1.10 mm of insulation (core Ø 16.3 mm) and 3.3 mm inner and 9.9 mm outer sheath; outer diameter 64.0–72.5 mm, weight about 6,650 kg/km of which copper 4,610 kg/km (69 %). Rated current 297 A at 30 °C; at that load the voltage drop is 10.92 V per 100 m (2.73 % of 400 V) and the loss 5.43 kW per 100 m. Bending radius 290 mm fixed, 435 mm moving; gland M100, lug bolt M12. Short-circuit rating 17.16 kA for 1 s; permitted pull 14,900 N, free-hanging length 228 m.

4×150. This size has with a conductor of Ø 15.8 mm under 1.40 mm of insulation (core Ø 18.6 mm) and 3.6 mm inner and 9.8 mm outer sheath; outer diameter 70.0–79.5 mm, weight about 8,030 kg/km of which copper 5,760 kg/km (72 %). Rated current 342 A at 30 °C; at that load the voltage drop is 10.64 V per 100 m (2.66 % of 400 V) and the loss 5.77 kW per 100 m. Bending radius 318 mm fixed, 477 mm moving; gland M100, lug bolt M12. Short-circuit rating 21.45 kA for 1 s; permitted pull 18,270 N, free-hanging length 231 m.

Averaged over all sizes copper makes up 60 % of the cable weight; the share rises from 21 % at 4×1.5 to 72 % at 4×150, which is why the larger sizes are costed mostly on the copper market price.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

09 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 0.6/1 kV.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Laid-up core Ø mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
4×1.5	1.65	3.05	0.70	8.0	1.13	2.36	0.65	51
4×2.5	2.13	3.53	0.70	9.1	1.21	2.90	0.66	51
4×4	2.70	4.10	0.70	10.5	1.30	3.48	0.68	51
4×6	3.30	4.70	0.70	12.0	1.39	3.74	0.69	49
4×10	4.08	5.48	0.70	13.8	1.52	4.50	0.72	49
4×16	5.16	6.56	0.70	16.4	1.69	4.68	0.75	46
4×25	6.45	8.25	0.90	20.5	1.96	6.20	0.80	47
4×35	7.63	9.43	0.90	23.4	2.15	6.21	0.83	44
4×50	9.12	11.12	1.00	27.5	2.42	6.95	0.88	43
4×70	10.79	12.79	1.00	31.5	2.69	7.82	0.93	42
4×95	12.57	14.77	1.10	36.3	3.01	8.82	0.98	41
4×120	14.13	16.33	1.10	40.0	3.25	9.86	1.03	41
4×150	15.80	18.60	1.40	45.5	3.62	9.81	1.10	39

10 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
4×1.5	17.3	M32	M5	10	35
4×2.5	19.8	M32	M5	10	40
4×4	22.8	M32	M5	10	45
4×6	25.0	M32	M5	11	50
4×10	29.0	M40	M6	11	60
4×16	32.5	M50	M6	12	65
4×25	41.0	M63	M8	14	80
4×35	44.5	M75	M8	16	90
4×50	51.0	M75	M10	19	100
4×70	58.0	M85	M10	26	115
4×95	66.0	M90	M12	31	130
4×120	72.5	M100	M12	35	145
4×150	79.5	M100	M12	41	160

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

11 Comparison with Related Variants at Size 4×25

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet NSHTöu 4× 0.6/1 kV	–	41.0	2,120	4,660	111
NSHTöu 3G 0.6/1 kV 3G25	core configuration	37.0 (-10%)	1,640 (-23%)	3,890 (-17%)	131 (+18%)
NSHTöu 4G 0.6/1 kV 4G25	core configuration	41.0 (+0%)	2,120 (+0%)	4,660 (+0%)	131 (+18%)
NSHTöu 4× 0.6/1 kV 4×25	tinned vs bare copper	41.0 (+0%)	2,120 (+0%)	4,660 (+0%)	110 (-1%)
NSHTöu 4× 0.6/1 kV 4×25	low-temperature sheath	41.0 (+0%)	2,120 (+0%)	4,660 (+0%)	111 (+0%)
NSHTöu 4× 0.66/1.14 kV 4×25	voltage class	42.5 (+4%)	2,230 (+5%)	4,840 (+4%)	111 (+0%)
NSHTöu 3× 0.6/1 kV 3×25	core configuration	37.0 (-10%)	1,640 (-23%)	3,890 (-17%)	131 (+18%)
NSHTöu 5× 0.6/1 kV 5×25	core configuration	45.0 (+10%)	2,590 (+22%)	5,500 (+18%)	98 (-12%)
NSHTöu 5G 0.6/1 kV 5G25	core configuration	45.0 (+10%)	2,590 (+22%)	5,500 (+18%)	111 (+0%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

12 Standards and Testing

Standard	Scope
DIN VDE 0250-814	Rubber-insulated flexible cable NSHTöu, 0.6/1 kV
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN VDE 0207-20 / -21	Rubber insulation and sheath compounds
DIN VDE 0293-308	Core identification
DIN VDE 0298-3 / -4	Application: bending, tensile load; current-carrying capacity
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation, single cable

Routine and type tests

- AC voltage test on every drum length (routine test): 3 kV, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors
- Flame propagation test (IEC 60332-1-2) and mineral-oil resistance on type-test samples
- Tensile test of the finished cable and inspection of the aramid braid coverage (type test)
- Bending and torsion tests for reeling duty (type test)

Test documentation: every delivery is accompanied by a test certificate from FeiChun’s own laboratory. Third-party witnessed tests can be arranged at the buyer’s cost.

The design follows DIN VDE 0250-814. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

13 Installation, Marking and Delivery

Installation guidance

- Introduce the pulling or hanging load only through a strain-relief clamp or cable grip that holds the sheath and the aramid braid.
- Respect the dynamic limit of 30 N/mm² on the copper cross-section; the permanent limit is 15 N/mm².
- On a reel use a core diameter of at least 2 × the reel bending radius in the table and guide the cable without cross-over.
- Limit torsion by guiding the cable straight; release twist before re-spooling.
- Fit protective sleeves at the entry to the reel or trolley to avoid sheath wear.
- Terminate the protective conductors at both ends.

Sheath marking

FEICHUN NSHTöu [cross-section] 0.6/1 kV [year] [serial no.] [metre mark]

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: NSHTöu 4×25 0.6/1 kV – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (bare copper), length per piece, required standards and installation conditions.

14 Certification and Quality

All cable is subject to FeiChun's quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

15 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- NSHTöu 3G 0.6/1 kV – core configuration, CR rubber, low-temp
- NSHTöu 4G 0.6/1 kV – core configuration, CR rubber, low-temp
- NSHTöu 4× 0.6/1 kV – tinned vs bare copper, CR rubber, low-temp, tinned
- NSHTöu 4× 0.6/1 kV – low-temperature sheath, CR rubber
- NSHTöu 4× 0.66/1.14 kV – voltage class, CR rubber, low-temp
- NSHTöu 3× 0.6/1 kV – core configuration, CR rubber, low-temp
- NSHTöu 5× 0.6/1 kV – core configuration, CR rubber, low-temp
- NSHTöu 5G 0.6/1 kV – core configuration, CR rubber, low-temp

Overview of all NSHTöu datasheets: NSHTöu Heavy Rubber Trailing Cables

Frequently asked questions

What does the T in NSHTöu stand for?
The T marks the tensile-bearing element of the trailing cable. In this datasheet it is realised as an aramid support braid between the inner and outer sheath.

What tensile load can the cable carry?
At the largest size, 4×150, the permitted pull is 18,270 N (15 N/mm² of the copper cross-section, plus the aramid braid).

What sizes are available for NSHTöu 4×?
13 sizes from 1.5 to 150 mm². The outer dimension of the largest size, 4×150, is 79.5 mm and the weight is about 8,030 kg/km.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

What current can 4×25 carry?
111 A in free air at 30 °C ambient, with the conductor at 90 °C. Other temperatures and grouping change the value; use the factors in section 04.

16 Trademark Notice and Intellectual Property

Cable type designations such as NSHTöu are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0331-EN
Revision 0 — first issue
Date 2 November 2026
Product NSHTöu 0.6/1 kV

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.