DIN VDE 0250-812 · HEAVY RUBBER-SHEATHED FLEXIBLE CABLE | 0.66/1.14 kV | 12 sizes | CR rubber | BARE COPPER | SCREENED

NSSHCöu 2× 0.66/1.14 kV

Heavy Rubber-Sheathed Flexible Cable 0.66/1.14 kV – 2 cores of equal cross-section in concentric layers with a short lay length. Polychloroprene rubber sheath. Complete technical data sheet: construction, dimensions, weights, current ratings, voltage drop and installation guidance for 12 sizes.

Document no. FC-TDS-VDE-2026-0247-EN · Revision 0 · Issued 2 November 2026 · Language: English

01 Application and Product Overview

NSSHCöu is the VDE designation of the heavy rubber-sheathed flexible cable (Gummischlauchleitung) for 0.6/1 kV. EPR-insulated cores of fine-wire class 5 copper are stranded together, bedded in a rubber inner sheath and protected by a thick, oil-resistant polychloroprene outer sheath that withstands crushing, abrasion and repeated bending. It is the established connection cable for mobile machines, portable switchgear and heavy tools on building sites, in quarries and in mines.

Design

The cores are insulated with a cross-linked EPR compound of type 3GI3, which permits a conductor temperature of 90 °C, and are stranded in layers with a short lay length. A rubber inner sheath fills the interstices and gives the stranded core a round, stable shape. The outer sheath is a polychloroprene compound of type 5GM5 to DIN VDE 0207-21. In the VDE designation the letters ö and u stand for oil resistance and flame retardancy; the suffix J marks a version with a green-yellow protective core, O a version without. In this datasheet J corresponds to the “G” configurations and O to the “×” configurations.

Typical applications

- Mobile switchgear, site distribution boards and portable generators on building sites and in quarries
- Feeder cables for electric tools, concrete pumps, mixers, crushers and conveyor drives that are moved regularly
- Underground and open-cast mining equipment that needs a robust connection cable of moderate length
- Cranes, hoists and loading equipment where the cable is dragged, stepped on or run over
- Machine tools and switch cabinets in dry, damp and wet areas, indoors and outdoors
- Converter-fed drives where the screened design limits electromagnetic interference
- Battery and DC-motor connections of industrial trucks and mining vehicles
- Replacement and extension of existing NSSHöu cabling in plants built to DIN VDE 0250-812

12 sizes	0.66/1.14 kV	+90 °C	CR rubber
Cross-section 1.5 – 120 mm²	Rated voltage U_0/U	Maximum conductor temperature	Sheath: CR rubber

Key features

- Thick rubber double sheath (inner and outer) for high resistance to crushing, impact and abrasion
- EPR insulation rated for 90 °C at the conductor; short-circuit temperature 250 °C
- Oil-resistant to DIN EN 60811-404 and flame-retardant to IEC 60332-1-2
- Fine-wire class 5 conductors for flexibility and easy termination
- Suitable for outdoor use: resistant to weather, ozone and UV radiation
- Cores identified to DIN VDE 0293-308; green-yellow PE core in the J versions
- 12 sizes from 1.5 to 120 mm²; weight from 211 to 3,810 kg/km; copper from 29 to 2,300 kg/km

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Core layout and conductor

2 cores of equal cross-section in concentric layers with a short lay length. Core colours: brown, blue (DIN VDE 0293-308); no protective core is included. Two-core cables serve single-phase AC and DC supplies. The conductors are bare annealed copper. Bare copper has the lowest conductor resistance of the class 5 range and is the usual choice for dry and damp indoor use. Where the cable is exposed to salt, sulphur or permanent moisture, the tinned version of the same cable is preferable.

Standard background

DIN VDE 0250-812 is the national standard for the NSSHöu heavy rubber-sheathed flexible cable. It fixes the conductor class, the insulation and sheath compounds, the wall thicknesses, the dimension limits and the routine and type tests. The harmonised H07RN-F cable covers lighter duty at 450/750 V; NSSHöu is the step up for 0.6/1 kV systems and for heavier mechanical loading.

The standard sheath compound is flexible down to 25 °C in motion and 40 °C in fixed installation. For regular use below this limit select the low-temperature grade of the same cable.


The overall screen is a tinned-copper wire braid between the inner and outer sheath. It reduces emitted and received interference in converter-fed drives and lets the cable meet the EMC requirements of the installation. A 360° termination of the screen at both ends gives the best effect; a screen that is terminated with a pigtail loses most of its benefit at high frequencies.

0.66/1.14 kV is the rating for the 1,000 V (1.14 kV) systems used in mining and in heavy industry; it has a slightly thicker insulation than the 0.6/1 kV version. The test voltage is 3 kV.

02 Construction

FEICHUN · CROSS-SECTION A–A · 0.66/1.14 kV

NSSHCöu
Sample size 2×16 · Rev 0 · Illustrative, not to scale



No.	Component	Material
1	Conductor	Bare annealed fine-wire copper, class 5 to IEC 60228 / DIN VDE 0295
2	Insulation	EPR rubber, type 3GI3 (90 °C)
3	Filler and binder tape	Rubber or compound filler with polyester binder tape
4	Inner sheath	Rubber compound, extruded over the stranded core
5	Overall screen	Bare copper-wire braid, coverage ≥ 85 %
6	Outer sheath	Polychloroprene (CR) rubber, type 5GM5

The drawing shows size 2×16. Other sizes have the same construction with scaled dimensions; the layout of every size is checked for non-overlap of all elements.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Construction details

Conductor	Bare annealed fine-wire copper, class 5 to DIN VDE 0295 / IEC 60228
Insulation	EPR rubber, type 3GI3 (90 °C), maximum conductor temperature 90 °C
Core identification	Brown, blue to DIN VDE 0293-308
Stranding	Cores in concentric layers with a short lay length
Overall screen	Bare copper-wire braid, coverage ≥ 85 %, between inner and outer sheath
Inner sheath	Rubber compound; thickness about 1.5 mm at this size
Outer sheath	Polychloroprene (CR) rubber, type 5GM5; thickness about 4.3 mm at this size

03 Electrical, Thermal and Mechanical Characteristics

Electrical data

Rated voltage U_0/U	0.66/1.14 kV AC
Test voltage	3 kV AC, 5 min
Maximum operating voltage, three-phase	1.2 kV
Maximum operating voltage, DC (core-earth / core-core)	1.0/1.8 kV
Current-carrying capacity	Design values by the method of DIN VDE 0298-4, free air, 30 °C ambient
Conductor resistance	Maximum at 20 °C, class 5, bare

Thermal and mechanical data

Maximum conductor temperature	+90 °C
Maximum temperature at short circuit	+250 °C (5 s maximum)
Ambient temperature, fixed installation	−40 °C to +80 °C
Ambient temperature, in motion	−25 °C to +80 °C
Minimum bending radius	Fixed: 3 × D (D ≤ 12 mm), 4 × D (D > 12 mm); moving: 3 × D (D ≤ 8 mm), 4 × D (D ≤ 12 mm), 5 × D (D > 12 mm) (DIN VDE 0298-3)
Maximum tensile load	15 N/mm² continuous on the total copper cross-section
Flame propagation	IEC 60332-1-2 / DIN EN 60332-1-2
Halogen-free	No (CR rubber)
Mineral oil resistance	Resistant, DIN EN 60811-404
UV and ozone resistance	Resistant
Water	Damp and wet areas, spray water

© 2026 Anhui FeiChun Special Cable Co., Ltd.

04 Dimensions, Weights and Rated Data – 0.66/1.14 kV (12 sizes)

Type designation cores × mm²	FeiChun article no.	Cond. Ø max mm	Outer Ø min mm	Outer Ø max mm	Bend radius fixed mm	Bend radius moving mm	Weight approx. kg/km	Copper kg/km	Max. pull N	R_{20} max Ω/km	Rated current A	I_k (1 s) kA
2×1.5	FC-NSSH-0247-01	1.7	13.8	15.6	62	78	211	29	45	13.3	23	0.214
2×2.5	FC-NSSH-0247-02	2.2	15.7	17.8	71	89	289	48	75	7.98	31	0.357
2×4	FC-NSSH-0247-03	2.7	17.8	20.2	81	101	368	77	120	4.95	42	0.572
2×6	FC-NSSH-0247-04	3.3	19.5	22.2	89	111	450	115	180	3.30	54	0.858
2×10	FC-NSSH-0247-05	4.1	22.5	25.5	102	128	670	192	300	1.91	74	1.43
2×16	FC-NSSH-0247-06	5.2	25.0	28.5	114	142	1,000	307	480	1.21	99	2.29
2×25	FC-NSSH-0247-07	6.5	31.5	36.0	144	180	1,370	480	750	0.780	131	3.58
2×35	FC-NSSH-0247-08	7.7	34.0	38.5	154	192	1,810	670	1,050	0.554	162	5.00
2×50	FC-NSSH-0247-09	9.2	39.0	44.0	176	220	2,420	960	1,500	0.386	202	7.15
2×70	FC-NSSH-0247-10	10.8	43.5	49.5	198	248	2,500	1,340	2,100	0.272	250	10.01
2×95	FC-NSSH-0247-11	12.6	49.5	56.0	224	280	3,080	1,820	2,850	0.206	302	13.59
2×120	FC-NSSH-0247-12	14.2	54.5	62.0	248	310	3,810	2,300	3,600	0.161	350	17.16

Current-carrying capacity: design values by the method of DIN VDE 0298-4, free air, 30 °C ambient; for other ambient temperatures use the factors below. Copper weight = 9.6 kg/(km·mm²) of copper cross-section (VDE copper index). Pull force = 15 N/mm² × total copper cross-section of the power cores. Diameters, dimensions and weights are nominal design values calibrated to published type tables; they vary within manufacturing tolerances. Confirm critical dimensions before dimensioning reels, glands or festoon systems. Other sizes and configurations are produced to order.

Ambient temperature factors (conductor 90 °C)

°C	20	25	30	35	40	45	50	55	60
Factor	1.08	1.04	1.00	0.96	0.91	0.87	0.82	0.76	0.71

Short-circuit current rating

I_k = 0.143 kA/mm² × cross-section of the power core (conductor 90 °C → 250 °C). For another duration t: $I_{k,t} = I_{k,1s} / \sqrt{t}$ (0.1 s ≤ t ≤ 5 s).

05 Voltage Drop, Losses and Short-Circuit Data

Voltage drop per 100 m of cable at rated current with the conductor at 90 °C, cos φ = 0.8 and reactance 0.08 Ω/km (three-phase). The percentage refers to a system voltage of 690 V. Loss is the total I²R loss of the loaded cores per 100 m. The short-circuit columns give the permitted current for four durations.

Type designation cores × mm²	Rated current A	R at 90 °C Ω/km	Voltage drop V / 100 m	Voltage drop % of 690 V	Loss kW / 100 m	I_k 0.1 s kA	I_k 0.5 s kA	I_k 1 s kA	I_k 3 s kA
2×1.5	23	17.0	54.24	7.86	2.69	0.678	0.303	0.214	0.124
2×2.5	31	10.2	43.97	6.37	2.93	1.13	0.506	0.357	0.206
2×4	42	6.31	37.08	5.37	3.34	1.81	0.809	0.572	0.330
2×6	54	4.21	31.93	4.63	3.68	2.71	1.21	0.858	0.495
2×10	74	2.44	25.59	3.71	4.00	4.52	2.02	1.43	0.826
2×16	99	1.54	21.99	3.19	4.54	7.24	3.24	2.29	1.32
2×25	131	0.995	19.14	2.77	5.12	11.31	5.06	3.58	2.06
2×35	162	0.706	17.20	2.49	5.56	15.83	7.08	5.00	2.89
2×50	202	0.492	15.46	2.24	6.02	22.61	10.11	7.15	4.13
2×70	250	0.347	14.09	2.04	6.50	31.65	14.16	10.01	5.78
2×95	302	0.263	13.50	1.96	7.19	42.96	19.21	13.59	7.84
2×120	350	0.205	12.87	1.86	7.54	54.26	24.27	17.16	9.91

06 Selection Guide and Sizing Aid

NSSHCöu 2× covers 12 sizes. The smallest, 2×1.5, has an outer diameter of up to 15.6 mm and weighs about 211 kg/km; the largest, 2×120, has an outer diameter of up to 62.0 mm and weighs about 3,810 kg/km, 18.1 times as much. Across the range the rated current rises from 23 A to 350 A at 30 °C and the fixed bending radius from 62 mm to 248 mm.

Example 1. A circuit draws 50 A continuously at 40 °C ambient temperature, in a group of two cables. Temperature factor 0.91, grouping factor 0.80: required table current = 50 / (0.91 × 0.80) = 69 A. The smallest suitable size is 2×10 with 74 A.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

Example 2. A circuit draws 178 A continuously at 35 °C ambient temperature, on its own. Temperature factor 0.96: required table current = 178 / (0.96) = 186 A. The smallest suitable size is 2×50 with 202 A.

07 Engineering Profile by Size

Every size of NSSHCöu 2× with the dimensions that decide how it behaves in a circuit: layers, weight, copper share, heat, voltage drop, bending, termination and pull.

2×1.5. This size has with a conductor of Ø 1.7 mm under 0.80 mm of insulation (core Ø 3.3 mm) and 1.1 mm inner and 2.3 mm outer sheath; outer diameter 13.8–15.6 mm, weight about 211 kg/km of which copper 29 kg/km (14 %). Rated current 23 A at 30 °C; at that load the voltage drop is 54.24 V per 100 m (7.86 % of 690 V) and the loss 2.69 kW per 100 m. Bending radius 62 mm fixed, 78 mm moving; gland M25, lug bolt M5. Short-circuit rating 0.214 kA for 1 s; permitted pull 45 N, free-hanging length 21 m.

2×2.5. This size has with a conductor of Ø 2.1 mm under 0.80 mm of insulation (core Ø 3.7 mm) and 1.1 mm inner and 2.7 mm outer sheath; outer diameter 15.7–17.8 mm, weight about 289 kg/km of which copper 48 kg/km (17 %). Rated current 31 A at 30 °C; at that load the voltage drop is 43.97 V per 100 m (6.37 % of 690 V) and the loss 2.93 kW per 100 m. Bending radius 71 mm fixed, 89 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.357 kA for 1 s; permitted pull 75 N, free-hanging length 26 m.

2×4. This size has with a conductor of Ø 2.7 mm under 0.80 mm of insulation (core Ø 4.3 mm) and 1.2 mm inner and 3.3 mm outer sheath; outer diameter 17.8–20.2 mm, weight about 368 kg/km of which copper 77 kg/km (21 %). Rated current 42 A at 30 °C; at that load the voltage drop is 37.08 V per 100 m (5.37 % of 690 V) and the loss 3.34 kW per 100 m. Bending radius 81 mm fixed, 101 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.572 kA for 1 s; permitted pull 120 N, free-hanging length 33 m.

2×6. This size has with a conductor of Ø 3.3 mm under 0.80 mm of insulation (core Ø 4.9 mm) and 1.3 mm inner and 3.5 mm outer sheath; outer diameter 19.5–22.2 mm, weight about 450 kg/km of which copper 115 kg/km (26 %). Rated current 54 A at 30 °C; at that load the voltage drop is 31.93 V per 100 m (4.63 % of 690 V) and the loss 3.68 kW per 100 m. Bending radius 89 mm fixed, 111 mm moving; gland M32, lug bolt M5. Short-circuit rating 0.858 kA for 1 s; permitted pull 180 N, free-hanging length 40 m.

2×10. This size has with a conductor of Ø 4.1 mm under 0.80 mm of insulation (core Ø 5.7 mm) and 1.4 mm inner and 4.1 mm outer sheath; outer diameter 22.5–25.5 mm, weight about 670 kg/km of which copper 192 kg/km (29 %). Rated current 74 A at 30 °C; at that load the voltage drop is 25.59 V per 100 m (3.71 % of 690 V) and the loss 4.00 kW per 100 m. Bending radius 102 mm fixed, 128 mm moving; gland M40, lug bolt M6. Short-circuit rating 1.43 kA for 1 s; permitted pull 300 N, free-hanging length 45 m.

2×16. This size has with a conductor of Ø 5.2 mm under 0.80 mm of insulation (core Ø 6.8 mm) and 1.5 mm inner and 4.3 mm outer sheath; outer diameter 25.0–28.5 mm, weight about 1,000 kg/km of which copper 307 kg/km (31 %). Rated current 99 A at 30 °C; at that load the voltage drop is 21.99 V per 100 m (3.19 % of 690 V) and the loss 4.54 kW per 100 m. Bending radius 114 mm fixed, 142 mm moving; gland M40, lug bolt M6. Short-circuit rating 2.29 kA for 1 s; permitted pull 480 N, free-hanging length 48 m.

2×25. This size has with a conductor of Ø 6.5 mm under 1.10 mm of insulation (core Ø 8.7 mm) and 1.8 mm inner and 5.7 mm outer sheath; outer diameter 31.5–36.0 mm, weight about 1,370 kg/km of which copper 480 kg/km (35 %). Rated current 131 A at 30 °C; at that load the voltage drop is 19.14 V per 100 m (2.77 % of 690 V) and the loss 5.12 kW per 100 m. Bending radius 144 mm fixed, 180 mm moving; gland M50, lug bolt M8. Short-circuit rating 3.58 kA for 1 s; permitted pull 750 N, free-hanging length 55 m.

2×35. This size has with a conductor of Ø 7.6 mm under 1.10 mm of insulation (core Ø 9.8 mm) and 1.9 mm inner and 5.6 mm outer sheath; outer diameter 34.0–38.5 mm, weight about 1,810 kg/km of which copper 670 kg/km (37 %). Rated current 162 A at 30 °C; at that load the voltage drop is 17.20 V per 100 m (2.49 % of 690 V) and the loss 5.56 kW per 100 m. Bending radius 154 mm fixed, 192 mm moving; gland M63, lug bolt M8. Short-circuit rating 5.00 kA for 1 s; permitted pull 1,050 N, free-hanging length 59 m.

2×50. This size has with a conductor of Ø 9.1 mm under 1.20 mm of insulation (core Ø 11.5 mm) and 2.2 mm inner and 6.3 mm outer sheath; outer diameter 39.0–44.0 mm, weight about 2,420 kg/km of which copper 960 kg/km (40 %). Rated current 202 A at 30 °C; at that load the voltage drop is 15.46 V per 100 m (2.24 % of 690 V) and the loss 6.02 kW per 100 m. Bending radius 176 mm fixed, 220 mm moving; gland M63, lug bolt M10. Short-circuit rating 7.15 kA for 1 s; permitted pull 1,500 N, free-hanging length 63 m.

2×70. This size has with a conductor of Ø 10.8 mm under 1.20 mm of insulation (core Ø 13.2 mm) and 2.4 mm inner and 7.0 mm outer sheath; outer diameter 43.5–49.5 mm, weight about 2,500 kg/km of which copper 1,340 kg/km (54 %). Rated current 250 A at 30 °C; at that load the voltage drop is 14.09 V per 100 m (2.04 % of 690 V) and the loss 6.50 kW per 100 m. Bending radius 198 mm fixed, 248 mm moving; gland M75, lug bolt M10. Short-circuit rating 10.01 kA for 1 s; permitted pull 2,100 N, free-hanging length 85 m.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

2×95. This size has with a conductor of Ø 12.6 mm under 1.30 mm of insulation (core Ø 15.2 mm) and 2.7 mm inner and 7.8 mm outer sheath; outer diameter 49.5–56.0 mm, weight about 3,080 kg/km of which copper 1,820 kg/km (59 %). Rated current 302 A at 30 °C; at that load the voltage drop is 13.50 V per 100 m (1.96 % of 690 V) and the loss 7.19 kW per 100 m. Bending radius 224 mm fixed, 280 mm moving; gland M85, lug bolt M12. Short-circuit rating 13.59 kA for 1 s; permitted pull 2,850 N, free-hanging length 94 m.

2×120. This size has with a conductor of Ø 14.1 mm under 1.30 mm of insulation (core Ø 16.7 mm) and 2.9 mm inner and 8.7 mm outer sheath; outer diameter 54.5–62.0 mm, weight about 3,810 kg/km of which copper 2,300 kg/km (60 %). Rated current 350 A at 30 °C; at that load the voltage drop is 12.87 V per 100 m (1.86 % of 690 V) and the loss 7.54 kW per 100 m. Bending radius 248 mm fixed, 310 mm moving; gland M85, lug bolt M12. Short-circuit rating 17.16 kA for 1 s; permitted pull 3,600 N, free-hanging length 96 m.

Averaged over all sizes copper makes up 46 % of the cable weight; the share rises from 14 % at 2×1.5 to 60 % at 2×120, which is why the larger sizes are costed mostly on the copper market price.

08 Construction Dimensions by Size

Wall thicknesses and diameters of the layers at each size, taken from the validated cross-section layout; the overall diameter in section 04 is the sum of these layers within tolerance. The insulation wall follows the voltage class 0.66/1.14 kV.

Type designation cores × mm²	Conductor Ø mm	Core Ø over insulation, mm	Insulation wall mm	Laid-up core Ø mm	Inner sheath mm	Outer sheath mm	Screen + braid mm	Sheath share of Ø, %
2×1.5	1.65	3.25	0.80	7.1	1.07	2.28	0.45	52
2×2.5	2.13	3.73	0.80	8.1	1.13	2.75	0.45	52
2×4	2.70	4.30	0.80	9.2	1.21	3.26	0.45	52
2×6	3.30	4.90	0.80	10.4	1.29	3.48	0.45	50
2×10	4.08	5.68	0.80	12.0	1.39	4.12	0.45	50
2×16	5.16	6.76	0.80	14.1	1.54	4.26	0.45	47
2×25	6.45	8.65	1.10	17.9	1.79	5.65	0.45	47
2×35	7.63	9.83	1.10	20.3	1.94	5.64	0.45	44
2×50	9.12	11.52	1.20	23.6	2.17	6.26	0.45	43
2×70	10.79	13.19	1.20	27.0	2.39	6.99	0.45	42
2×95	12.57	15.17	1.30	30.9	2.65	7.83	0.45	41
2×120	14.13	16.73	1.30	34.1	2.86	8.71	0.45	41

09 Termination Planning (indicative)

Type designation cores × mm²	Outer Ø or W × H mm	Cable gland thread	Lug / ferrule bolt	Strip length mm	Straight length behind gland, mm
2×1.5	15.6	M25	M5	10	30
2×2.5	17.8	M32	M5	10	35
2×4	20.2	M32	M5	10	40
2×6	22.2	M32	M5	11	45
2×10	25.5	M40	M6	11	50
2×16	28.5	M40	M6	12	55
2×25	36.0	M50	M8	14	70
2×35	38.5	M63	M8	16	75
2×50	44.0	M63	M10	19	90
2×70	49.5	M75	M10	26	100
2×95	56.0	M85	M12	31	110
2×120	62.0	M85	M12	35	125

Gland threads, lug bolts and strip lengths are planning guides computed from the dimensions above; confirm them with the accessory manufacturer.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

10 Comparison with Related Variants at Size 2×16

Variant	Differs in	Outer Ø / H mm	Weight kg/km	Pull N	Current A
This datasheet NSSHCöu 2× 0.66/1.14 kV	–	28.5	1,000	480	99
NSSHCöu 3× 0.66/1.14 kV 3×16	core configuration	29.5 (+4%)	1,230 (+23%)	720 (+50%)	99 (+0%)
NSSHCöu 3G 0.66/1.14 kV 3G16	core configuration	29.5 (+4%)	1,230 (+23%)	720 (+50%)	99 (+0%)
NSSHCöu 2× 0.66/1.14 kV 2×16	tinned vs bare copper	28.5 (+0%)	1,000 (+0%)	480 (+0%)	98 (-1%)
NSSHCöu 2× 0.66/1.14 kV 2×16	low-temperature sheath	28.5 (+0%)	1,000 (+0%)	480 (+0%)	99 (+0%)
NSSHöu 2× 0.66/1.14 kV 2×16	overall screen	27.5 (-4%)	900 (-10%)	480 (+0%)	99 (+0%)
NSSHCöu 2× 0.6/1 kV 2×16	voltage class	27.5 (-4%)	960 (-4%)	480 (+0%)	99 (+0%)
NSSHCöu 4× 0.66/1.14 kV 4×16	core configuration	33.0 (+16%)	1,580 (+58%)	960 (+100%)	84 (-15%)
NSSHCöu 4G 0.66/1.14 kV 4G16	core configuration	33.0 (+16%)	1,580 (+58%)	960 (+100%)	99 (+0%)

Percentages show the change against this datasheet; where a variant does not offer the exact size, the nearest listed size is used.

11 Standards and Testing

Standard	Scope
DIN VDE 0250-812	Rubber-insulated flexible cable NSSHöu, 0.6/1 kV
DIN VDE 0295 / IEC 60228	Conductors, class 5
DIN VDE 0207-20 / -21	Rubber insulation and sheath compounds (3GI3, 5GM5)
DIN VDE 0293-308	Core identification
DIN VDE 0298-3 / -4	Application: bending, tensile load; current-carrying capacity
DIN EN 60811-404	Mineral oil resistance of sheath
DIN EN 60332-1-2 / IEC 60332-1-2	Flame propagation, single cable

Routine and type tests

- AC voltage test on every drum length (routine test): 3 kV, 5 min
- Conductor resistance and checks of dimensions, insulation thickness and sheath thickness
- Continuity of conductors
- Flame propagation test (IEC 60332-1-2) and mineral-oil resistance on type-test samples

Test documentation: every delivery is accompanied by a test certificate from FeiChun’s own laboratory. Third-party witnessed tests can be arranged at the buyer’s cost.

The design follows DIN VDE 0250-812. This datasheet does not claim the VDE approval mark; mark or approval certificates, where required for a project, are arranged on request and apply only to the type tested.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

12 Installation, Marking and Delivery

Installation guidance

- Do not exceed the permissible tensile load of 15 N/mm² of the total copper cross-section; use a cable grip that holds the sheath, never the conductors.
- Keep the bending radius at or above the values in section 04; for free movement use 3 × D up to 8 mm, 4 × D up to 12 mm and 5 × D above 12 mm outer diameter.
- Lay the cable without kinks and unwind it completely from the reel before loading it above 50 % of the rated current.
- Use cable glands whose clamping range covers the maximum outer diameter and seal the cable entry to the enclosure rating.
- Protect the cable against permanent running-over by vehicles; where this cannot be avoided use cable ramps or protective ducts.
- Leave the green-yellow protective core slightly longer than the power cores, so that it is the last to be loaded if the cable is pulled at the terminal.

Sheath marking

```
FEICHUN NSSHCöu [cross-section] 0.66/1.14 kV [year] [serial no.] [metre mark]
```

Packing and delivery

Drum	Steel or fumigated wooden drums; cable ends sealed with heat-shrink caps
Delivery length	As ordered, in one continuous length without joints
Lead time	2–3 weeks after technical approval
Warranty	At least 3 years against manufacturing defects
Drum label	Type, cross-section, length, gross/net weight, batch no., drum no.

Ordering information

Order example: NSSHCöu 2×16 0.66/1.14 kV – 500 m on one drum. When requesting a quotation, state the cable type, configuration, cross-section, voltage, conductor (bare copper), length per piece, required standards and installation conditions.

13 Certification and Quality

All cable is subject to FeiChun’s quality control, with routine testing over 100 % of the delivered length. Declarations of conformity, type-test reports and third-party tests (for example for a mine, a tunnel or a rail project) are provided per project requirement; copies of the records are available on request. FeiChun holds CE, EAC and UKCA documentation for certain product groups. Whether a certificate covers this specific construction must be confirmed with FeiChun before it is quoted in a tender.

VDE, mine-specific (for example coal-mine safety marks, MSHA) and ATEX / IECEx approvals are not implied by this datasheet. They depend on the project, the machine and the country and are arranged with the end user.

14 Related Datasheets and Frequently Asked Questions

Variants of this cable with a different configuration, conductor, temperature grade, screen or voltage. All datasheets are PDF files.

- NSSHCöu 3× 0.66/1.14 kV – core configuration, CR rubber
- NSSHCöu 3G 0.66/1.14 kV – core configuration, CR rubber
- NSSHCöu 2× 0.66/1.14 kV – tinned vs bare copper, CR rubber, tinned
- NSSHCöu 2× 0.66/1.14 kV – low-temperature sheath, CR rubber, low-temp
- NSSHöu 2× 0.66/1.14 kV – overall screen, CR rubber
- NSSHCöu 2× 0.6/1 kV – voltage class, CR rubber
- NSSHCöu 4× 0.66/1.14 kV – core configuration, CR rubber
- NSSHCöu 4G 0.66/1.14 kV – core configuration, CR rubber

Overview of all NSSHöu datasheets: NSSHöu Heavy Rubber-Sheathed Flexible Cables

Frequently asked questions

Which cable is meant by NSSHöu?
NSSHöu is the VDE designation of the heavy rubber-sheathed flexible cable to DIN VDE 0250-812, rated 0.6/1 kV, with EPR insulation and a polychloroprene sheath.

What is the difference between the -J and the -O version?
The J version contains a green-yellow protective core; the O version does not. NSSHCöu 2× is the O (without PE core) version.

© 2026 Anhui FeiChun Special Cable Co., Ltd.

What sizes are available for NSSHCöu 2×?

12 sizes from 1.5 to 120 mm². The outer dimension of the largest size, 2×120, is 62.0 mm and the weight is about 3,810 kg/km.

What current can 2×25 carry?

131 A in free air at 30 °C ambient, with the conductor at 90 °C. Other temperatures and grouping change the value; use the factors in section 04.

15 Trademark Notice and Intellectual Property

Cable type designations such as NSSHCöu are standardised, descriptive designations defined in DIN VDE and EN standards; they are used to state which standard this product is designed to. References to other manufacturers' trade names, where made, serve only for technical comparison; FeiChun Cables is not affiliated with them.

© 2026 Anhui FeiChun Special Cable Co., Ltd. — All rights reserved. This document, including its drawings, tables and layout, is the intellectual property of FeiChun and is protected under the Copyright Law and the Anti-Unfair Competition Law of the People's Republic of China and the Copyright Act 1968 (Cth) of Australia. Reproduction, distribution or modification of the whole or any part without written consent is prohibited. Technical data may change without notice as part of continuous product improvement.

Technical and commercial contacts

Anhui FeiChun Special Cable Co., Ltd.
International Business Department
Park No. 1, Private Science and Technology Park, Hefei National Economic and Technological Development Zone, Hefei, Anhui, China
Technical support: Tech@feichuncables.com
Zihao Yang, Global Sales Manager: zihao.yang@feichuncables.com
WhatsApp: +86 138 5512 3218
Web: www.feichuncables.com

Document control

Document no. FC-TDS-VDE-2026-0247-EN
Revision 0 — first issue
Date 2 November 2026
Product NSSHCöu 0.66/1.14 kV

Prepared — Engineering | Checked — QC | Approved — International Business

© 2026 Anhui FeiChun Special Cable Co., Ltd.