




# FEICHUN SPECIAL CABLES

Website Address [www.feichuncables.com](http://www.feichuncables.com)  
 Whatsapp Account **+86 138 5608 5607 & +86 138 5512 3218**  
 Email Address [ziyu.huang@feichuncables.com](mailto:ziyu.huang@feichuncables.com) & [zihao.yang@feichuncables.com](mailto:zihao.yang@feichuncables.com)

## VDE 0250 Open-Cast Mining Cable

NTMTW0EU 0.6/1kV Mine Hoist Cable

8x2.5ST+10x (2x1FM)C



## APPLICATIONS

Type NTMTW0EU 0.6/1kV Mine Hoist Cables are used as suspended cables for intrinsically safe control of user-operated mine hoists (lifts) with telephonic connection in underground mines. These cables ensure reliable and safe communication and control in challenging mining environments.

## STANDARDS

VDE 0250 Part 813

## CABLE CONSTRUCTION

The cable consists of flexible stranded tinned copper conductors, compliant with Class 5 of DIN VDE 0295.

The insulation is made of EPR type 3GI3. It features a central steel support element for added strength.

An anti-torsion textile braid is incorporated to prevent twisting, and the outer sheath is made of PCP rubber type 5GM5.

## DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Overall Diameter (min.)	Overall Diameter (max.)	Approx. Weight
No.×mm <sup>2</sup>	mm	mm	kg/km
8x2.5ST+10x (2x1FM)C	34	37.5	1450